

Title (en)

QUICK CLAMPING DEVICE FOR A PORTABLE MACHINE TOOL, IN PARTICULAR AN ANGLE GRINDER, COMPRISING AT LEAST ONE OUTPUT SHAFT THAT CAN BE ROTATABLY DRIVEN

Title (de)

SCHNELLSPANNVORRICHTUNG FÜR EINE ZUMINDEST EINE ROTIEREND ANTREIBBARE ABTRIEBSWELLE AUFWEISENDE TRAGBARE WERKZEUGMASCHINE, INSbesondere WINKELSCHLEIFMASCHINE

Title (fr)

DISPOSITIF DE FIXATION RAPIDE POUR MACHINE-OUTIL PORTATIVE, EN PARTICULIER UNE MEULEUSE D'ANGLE DOTÉE D'AU MOINS ARBRE DE SORTIE SUSCEPTIBLE D'ÊTRE ENTRAÎNÉ EN ROTATION

Publication

EP 3529003 B1 20230726 (DE)

Application

EP 17778277 A 20171004

Priority

- DE 102016220367 A 20161018
- EP 2017075114 W 20171004

Abstract (en)

[origin: WO2018072997A1] The invention relates to a quick clamping device for a portable machine tool, in particular an angle grinder, comprising at least one output shaft (12a; 12b) that can be rotatably driven and that has at least one clamping unit (16a; 16b) which, for the purpose of fixing an insert bit (18a) to the output shaft (12a; 12b) without using tools, comprises at least one movably mounted clamping element (20a, 22a; 20b, 22b) for applying a clamping force to the insert bit (18a) in a clamping position of the clamping element (20a, 22a; 20b, 22b), and further has at least one operating unit (24a; 24b) for moving the clamping element (20a, 22a; 20b, 22b) into the clamping position and/or into a release position of the clamping element (20a, 22a; 20b, 22b), in which release position the insert bit (18a) can be removed from the clamping unit (16a; 16b) and/or the output shaft (12a; 12b). According to the invention, the quick clamping device comprises at least one securing unit (26a; 26b), in particular a self-locking unit and/or a detent unit, which is designed to prevent a movement of the clamping element (20a, 22a; 20b, 22b) from the clamping position into the release position of the clamping element (20a, 22a; 20b, 22b) at least under the action of a force decoupled from the control unit (24a; 24b) and acting on the clamping element (20a, 22a; 20b, 22b) in the direction of the release position of the clamping element (20a, 22a; 20b, 22b).

IPC 8 full level

B25F 5/02 (2006.01); **B24B 23/02** (2006.01); **B24B 45/00** (2006.01); **B25F 5/00** (2006.01); **B27B 5/32** (2006.01)

CPC (source: EP KR RU US)

B24B 23/02 (2013.01 - RU); **B24B 23/028** (2013.01 - EP KR US); **B24B 45/00** (2013.01 - RU); **B24B 45/006** (2013.01 - EP KR US);
B25F 5/00 (2013.01 - RU); **B25F 5/02** (2013.01 - EP KR); **B27B 5/32** (2013.01 - EP KR RU)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

DE 102016220367 A1 20180419; BR 112019007106 A2 20190625; BR 112019007106 B1 20231128; CN 109862998 A 20190607;
CN 109862998 B 20220111; EP 3529003 A1 20190828; EP 3529003 B1 20230726; JP 2019533581 A 20191121; JP 6802919 B2 20201223;
KR 102446010 B1 20220922; KR 20190071711 A 20190624; RU 2019114065 A 20201120; RU 2019114065 A3 20201204;
RU 2752491 C2 20210728; US 12017324 B2 20240625; US 2021276146 A1 20210909; WO 2018072997 A1 20180426

DOCDB simple family (application)

DE 102016220367 A 20161018; BR 112019007106 A 20171004; CN 201780064476 A 20171004; EP 17778277 A 20171004;
EP 2017075114 W 20171004; JP 2019519002 A 20171004; KR 20197011038 A 20171004; RU 2019114065 A 20171004;
US 201716341295 A 20171004