

Title (en)

ELECTRICAL INTERRUPTION SWITCH, IN PARTICULAR FOR INTERRUPTING HIGH CURRENTS AT HIGH VOLTAGES

Title (de)

ELEKTRISCHES UNTERBRECHUNGSSCHALTGLIED, INSBESONDERE ZUM UNTERBRECHEN VON HOHEN STRÖMEN BEI HOHEN SPANNUNGEN

Title (fr)

ORGANE ÉLECTRIQUE DE COMMANDE D'INTERRUPTION, EN PARTICULIER POUR L'INTERRUPTION DE FORTS COURANTS À DES HAUTES TENSIONS

Publication

EP 3555900 A1 20191023 (DE)

Application

EP 17787320 A 20171004

Priority

- DE 102016124176 A 20161213
- DE 2017100844 W 20171004

Abstract (en)

[origin: WO2018001420A1] The invention relates to an electrical interruption switch, in particular for interrupting high currents at high voltages, especially high direct currents, comprising a housing that surrounds a contact unit defining the current path through the interruption switch, and comprising a pyrotechnical material that includes a gas-generating and/or shock wave-generating activatable material; the contact unit includes a first terminal contact, a second terminal contact and a disconnection region; the pyrotechnical material and the contact unit are designed in such a way that a current which is to be interrupted can be fed to the contact unit via the first terminal contact and be discharged therefrom via the second terminal contact, or vice versa, and in such a way that the disconnection region is subjected to a gas pressure and/or a shock wave generated by the activatable material when the pyrotechnical material is ignited, causing the disconnection region to tear open, cave in or be severed and the at least one chamber in the interruption switch that is at least partly delimited by the disconnection region to fill at least substantially in its entirety with a filling material, preferably silicone oil, so that the disconnection region comes into contact with the filling material in order for the highest possible bursting pressure to be exerted on the disconnection region using a minimum amount of gas-generating mass or - if a shock wave-generating pyrotechnical compound is used - for said shock wave-generating pyrotechnical compound to be coupled with as little loss as possible to the disconnection region that is to be disconnected. An insertable central electrode relieves the disconnection point and/or indicates the successful triggering of the interruption switch following the initial disconnection.

IPC 8 full level

H01H 39/00 (2006.01)

CPC (source: EP US)

H01H 9/0066 (2013.01 - US); **H01H 9/02** (2013.01 - US); **H01H 39/006** (2013.01 - EP US); **H01H 85/0241** (2013.01 - US); **H01H 85/0241** (2013.01 - EP); **H01H 2039/008** (2013.01 - EP US)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

DE 102016124176 A1 20170126; CN 110073460 A 20190730; CN 110073460 B 20220304; DE 202017106261 U1 20171128; EP 3555900 A1 20191023; EP 3555900 B1 20230607; US 11062865 B2 20210713; US 2020211801 A1 20200702; WO 2018001420 A1 20180104

DOCDB simple family (application)

DE 102016124176 A 20161213; CN 201780077081 A 20171004; DE 2017100844 W 20171004; DE 202017106261 U 20171016; EP 17787320 A 20171004; US 201716468861 A 20171004