

Title (en)
SECURING DEVICE FOR CABLES

Title (de)
FESTLEGEVORRICHTUNG FÜR KABEL

Title (fr)
DISPOSITIF DE FIXATION POUR CÂBLES

Publication
EP 3560053 A1 20191030 (DE)

Application
EP 17822549 A 20171205

Priority
• DE 102016015226 A 20161221
• EP 2017001405 W 20171205

Abstract (en)
[origin: WO2018114036A1] The invention relates to a securing device comprising a rotational drive which is received in a housing (9). When the drive is actuated in a first rotational direction by hand, a securing part (11) can be moved in a translational manner into an end position retracted into the housing (9) against the effect of an energy storage unit (51) by means of threaded sections (19, 78, 79), and by actuating the drive in the opposite second rotational direction, the securing part extends out of the end position into at least one transfer position, in which the securing part (11) is released for translational retracting and extending movements and out of which the securing part (11) can be returned by actuating the drive in the first rotational direction against the effect of the energy storage unit (51), wherein the transfer position is formed by parts (80 to 84) of the threaded sections (19, 78, 79).

IPC 8 full level
H02G 3/22 (2006.01); **F16B 2/06** (2006.01); **F16G 11/00** (2006.01); **F16L 3/00** (2006.01); **H02G 3/30** (2006.01)

CPC (source: EP)
F16B 2/065 (2013.01); **F16B 2/241** (2013.01); **F16B 5/0685** (2013.01); **F16B 33/006** (2013.01); **F16B 33/02** (2013.01); **F16B 37/145** (2013.01); **H02G 3/22** (2013.01); **H02G 3/30** (2013.01)

Citation (search report)
See references of WO 2018114036A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
DE 102016015226 A1 20180621; EP 3560053 A1 20191030; WO 2018114036 A1 20180628

DOCDB simple family (application)
DE 102016015226 A 20161221; EP 17822549 A 20171205; EP 2017001405 W 20171205