

Title (en)

CORRUGATED SKID WITH OPTIMUM SUPPORT

Title (de)

GEWELLTE KUFE MIT OPTIMALER UNTERSTÜTZUNG

Title (fr)

PATIN ONDULÉ À SUPPORT OPTIMAL

Publication

EP 3568357 A1 20191120 (EN)

Application

EP 17899897 A 20171229

Priority

- US 201762444497 P 20170110
- US 2017069117 W 20171229

Abstract (en)

[origin: WO2018164760A1] A corrugated skid includes top and bottom blanks that are folded and assembled together to produce a double thickness deck supported by double thickness ribs that are folded downward from deck portions of each blank. The ribs of the top blank are split into three sections by two fork passages. The three sections penetrate through slots in the deck portion formed by the bottom blank. The double thickness ribs of the top and bottom blanks intersect with notches at a location below the deck. The double thickness ribs of the top and bottom blanks intersect each other near the center of the corrugated skid to form a continuous four-sided rib support rectangle that resists shifting between the top and bottom blanks.

IPC 8 full level

B65D 19/00 (2006.01); **B65D 19/02** (2006.01); **B65D 19/06** (2006.01); **B65D 19/12** (2006.01); **B65D 19/16** (2006.01); **B65D 19/18** (2006.01)

CPC (source: EP)

B65D 19/0071 (2013.01); **B65D 19/0075** (2013.01); **B65D 2519/00019** (2013.01); **B65D 2519/00054** (2013.01); **B65D 2519/00273** (2013.01);
B65D 2519/00293 (2013.01); **B65D 2519/00323** (2013.01); **B65D 2519/00338** (2013.01); **B65D 2519/00348** (2013.01);
B65D 2519/00567 (2013.01)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

WO 2018164760 A1 20180913; CN 110234574 A 20190913; EP 3568357 A1 20191120; EP 3568357 A4 20210106

DOCDB simple family (application)

US 2017069117 W 20171229; CN 201780085011 A 20171229; EP 17899897 A 20171229