

Title (en)
PLUG-TYPE CONNECTOR WITH INSULATION DISPLACEMENT CONTACT

Title (de)
STECKVERBINDER MIT SCHNEIDKLEMMKONTAKT

Title (fr)
CONNECTEUR À FICHE AVEC CONTACT AUTODÉNUDANT

Publication
EP 3625858 B1 20210428 (DE)

Application
EP 18726379 A 20180514

Priority
• DE 102017110544 A 20170515
• EP 2018062322 W 20180514

Abstract (en)
[origin: WO2018210716A1] The invention relates to a plug-type connector for connecting a cable comprising at least one wire to a respective plug contact (42), said connector comprising: a first housing part (1) with a first longitudinal axis (X), comprising at least one plug contact (42) and at least one insulation displacement contact (40) that is electrically connected to the respective plug contact (42) and embodied therewith such that it has an insertion slot with a cutting intake direction (Z) for a respective wire, for clamping the respective wire therein; a connection block (3) comprising a respective wire channel (32) for guiding the respective wire; and a second housing part (2) with a second longitudinal axis, comprising the connection block (3). According to the invention, the first housing part (1) and the second housing part (2) are interconnected by means of a common hinge connection with an axis of rotation; the hinge connection is designed such that the second housing part (2) can be pivoted out of a first position into a second position, about the axis of rotation towards the first housing part (1), the respective wire being insertable into the respective wire channel (32) of the connection block (3) in the first position, and, in the second position, the second housing part (2) starting to press the connection block with the respective wire guided in the respective wire channel (32) against the respective insulation displacement contact (40); and the hinge connection is designed such that the second housing part (2) can move on the first housing part (1), out of the second position into a third position in which the connection block (3) with the respective wire guided in the respective wire channel (32) is fully pressed onto the at least one insulation displacement contact. The hinge connection is also designed to allow an insertion movement out of the second position into the third position such that the second housing part (2) inserts the respective wire into the respective insulation displacement contact (40) in an exclusively translatory manner in the cutting intake direction (Z) towards the first housing part (1) .

IPC 8 full level
H01R 24/64 (2011.01); **H01R 4/2433** (2018.01); **H01R 13/506** (2006.01); **H01R 13/58** (2006.01)

CPC (source: EP KR US)
H01R 4/2433 (2013.01 - EP KR US); **H01R 13/506** (2013.01 - EP KR US); **H01R 13/582** (2013.01 - KR); **H01R 24/64** (2013.01 - EP KR); **H01R 13/582** (2013.01 - EP); **H01R 24/64** (2013.01 - US); **H01R 2107/00** (2013.01 - US)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
DE 102017110544 B3 20180719; CN 110622369 A 20191227; CN 110622369 B 20210226; EP 3625858 A1 20200325; EP 3625858 B1 20210428; KR 102248383 B1 20210506; KR 20200004413 A 20200113; US 11011859 B1 20210518; US 2021151908 A1 20210520; WO 2018210716 A1 20181122

DOCDB simple family (application)
DE 102017110544 A 20170515; CN 201880031943 A 20180514; EP 18726379 A 20180514; EP 2018062322 W 20180514; KR 20197036790 A 20180514; US 201816610881 A 20180514