

Title (en)  
METHOD FOR OPERATING AN AIR-JET SPINNING DEVICE, THREAD GUIDING CHANNEL, AND AIR-JET SPINNING MACHINE COMPRISING SUCH A THREAD GUIDING CHANNEL

Title (de)  
VERFAHREN ZUM BETREIBEN EINER LUFTSPINNVORRICHTUNG, FADENLEITKANAL UND LUFTSPINNMASCHINE UMFASSEND EINEN SOLCHEN FADENLEITKANAL

Title (fr)  
PROCÉDÉ POUR FAIRE FONCTIONNER UN ARRANGEMENT DE FILAGE À JET D'AIR, CANAL DE GUIDAGE DE FIL ET MÉTIER À FILER À JET D'AIR COMPRENANT UN TEL CANAL DE GUIDAGE DE FIL

Publication  
**EP 3652368 A2 20200520 (DE)**

Application  
**EP 18740594 A 20180713**

Priority  
• DE 102017115939 A 20170714  
• EP 2018069160 W 20180713

Abstract (en)  
[origin: WO2019012143A2] The invention relates to a method for operating an air-jet spinning device following an interruption in spinning, a thread guiding channel, and an air-jet spinning machine comprising such a thread guiding channel. A drawing frame for drawing a fibre band is connected upstream, in the running direction of said fibre band, of the air-jet spinning device, and a single-motor thread draw-off arrangement for drawing off a thread spun by the air-jet spinning device is arranged downstream. According to the invention, following an interruption in spinning, the end of the spun thread, which is wound onto a take-up bobbin, is picked up by a suction nozzle and transferred to a thread end preparation device connected downstream of the air-jet spinning device in the running direction of the fibre band; the thread end is processed in said thread end preparation device and subsequently transferred into the region of the outlet opening of the spinning cone; the thread end is conveyed pneumatically to the inlet opening of the spinning cone and positioned there, inside the air-jet spinning device, at a distance in front of said inlet opening; and the drawing frame of the work station in question is lifted up and the fibre band is thus conveyed through a fibre band guide of the nozzle block into the region of the inlet opening of the spinning cone and joined to the prepared end of the spun thread.

IPC 8 full level  
**D01H 1/115** (2006.01); **D01H 15/00** (2006.01)

CPC (source: EP US)  
**B65H 51/16** (2013.01 - US); **D01H 1/115** (2013.01 - EP US); **D01H 15/00** (2013.01 - EP); **D01H 15/002** (2013.01 - US)

Citation (search report)  
See references of WO 2019012143A2

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)  
BA ME

DOCDB simple family (publication)  
**WO 2019012143 A2 20190117; WO 2019012143 A3 20190328**; BR 112019026870 A2 20200630; CN 110892102 A 20200317; CN 110892102 B 20220408; DE 102017115939 A1 20190117; EP 3652368 A2 20200520; EP 3652368 B1 20220223; JP 2020527197 A 20200903; JP 7101755 B2 20220715; PT 3652368 T 20220510; TW 201908555 A 20190301; TW I770227 B 20220711; US 11753747 B2 20230912; US 11753748 B2 20230912; US 2020224337 A1 20200716; US 2022178052 A1 20220609

DOCDB simple family (application)  
**EP 2018069160 W 20180713**; BR 112019026870 A 20180713; CN 201880046356 A 20180713; DE 102017115939 A 20170714; EP 18740594 A 20180713; JP 2020501295 A 20180713; PT 18740594 T 20180713; TW 107124138 A 20180712; US 201816630937 A 20180713; US 202217681185 A 20220225