

Title (en)
BEVERAGE DISPENSER FOR OUTPUT OF BEVERAGE WITH VARIABLE TEMPERATURE

Title (de)
GETRÄNKESPENDER ZUR AUSGABE EINES GETRÄNKES MIT VARIABLER TEMPERATUR

Title (fr)
DISTRIBUTEUR DE BOISSONS POUR LA SORTIE DE BOISSONS AVEC UNE TEMPÉRATURE VARIABLE

Publication
EP 3712105 A1 20200923 (EN)

Application
EP 19164070 A 20190320

Priority
EP 19164070 A 20190320

Abstract (en)
A beverage dispenser (100), comprising:- an inlet for drawing a liquid from a source (102);- an outlet (132) for outputting a beverage to a portable user vessel (134);- a demineralization device (106) for demineralizing the liquid from the source having an input and an output, wherein the input of the demineralization device is coupled with the inlet;- a beverage preparation device (122, 124, 126) having an input and an output, wherein the input of the beverage preparation device (122, 124, 126) is coupled with the output of the demineralization device (106) and the output of the beverage preparation device (122, 124, 126) is coupled with the outlet;- a beverage tempering device (122) downstream of the demineralization device (106) and upstream of the outlet (132);- wherein beverage contacting elements in the tempering device and downstream of the tempering device define a tempered flow path; and- wherein at least 50 %, preferably, at least 75 %, more preferred at least 90 %, most preferred at least 95 % of the beverage contacting elements along the tempered flow path fulfill at least one of the following conditions:- the wall thickness of the beverage contacting elements is equal or smaller than 20 % of the width of the flow channel, preferably equal or smaller than 15 % of the width of the flow channel, more preferred equal or smaller than 10 % of the width of the flow channel, most preferred equal or smaller than 5 % of the width of the flow channel;- the wall thickness of the beverage contacting elements is equal or smaller than approximately 1 mm, preferably is equal or smaller than approximately 0.5 mm, more preferred is equal or smaller than approximately 0.3 mm.

IPC 8 full level
B67D 3/00 (2006.01); **B67D 1/00** (2006.01); **B67D 1/08** (2006.01)

CPC (source: EP)
B67D 1/0003 (2013.01); **B67D 1/0014** (2013.01); **B67D 1/08** (2013.01); **B67D 1/0804** (2013.01); **B67D 1/0857** (2013.01); **B67D 1/0895** (2013.01); **B67D 3/0058** (2013.01); **B67D 2001/075** (2013.01); **B67D 2210/00047** (2013.01); **B67D 2210/00049** (2013.01); **B67D 2210/00062** (2013.01); **B67D 2210/00118** (2013.01)

Citation (applicant)
EP 18207971.5 A

Citation (search report)
• [Y] WO 2010019891 A2 20100218 - DEKA PRODUCTS LP [US], et al
• [Y] WO 2008127113 A2 20081023 - SARA LEE DE NV [NL], et al
• [Y] DE 29818213 U1 19990107 - FELLER GMBH F [DE]
• [Y] AU 2010200211 B2 20160421 - CUB PTY LTD [AU]
• [Y] WO 2004058019 A1 20040715 - NESTEC SA [CH], et al
• [Y] WO 2013141253 A1 20130926 - DAIKIN IND LTD [JP]
• [A] EP 1930290 A1 20080611 - TDS TECH VERKAUFSHILFEN UND ZU [DE]
• [A] US 2007095091 A1 20070503 - CYR MICHAEL P [CA]
• [A] US 4171069 A 19791016 - CORNELIUS RICHARD T [US], et al

Cited by
JP2022060707A

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
EP 3712105 A1 20200923

DOCDB simple family (application)
EP 19164070 A 20190320