

Title (en)
STATOR/ROTOR DEVICE FOR ELECTRIC MOTORS, AND METHOD FOR PRODUCING A PLASTIC COATING OF A STATOR/ROTOR DEVICE

Title (de)
STATOR-/ROTORVORRICHTUNG FÜR ELEKTROMOTOREN UND VERFAHREN ZUR HERSTELLUNG EINER KUNSTSTOFFBESCHICHTUNG EINER STATOR-/ROTORVORRICHTUNG

Title (fr)
DISPOSITIF DE STATOR/ROTOR POUR MOTEURS ÉLECTRIQUES ET PROCÉDÉ DE FABRICATION D'UN REVÊTEMENT D'UN DISPOSITIF DE STATOR/ROTOR

Publication
EP 3729615 A1 20201028 (DE)

Application
EP 18845340 A 20181219

Priority

- DE 202017006523 U 20171220
- DE 2018000375 W 20181219

Abstract (en)
[origin: WO2019120354A1] The invention relates to a stator/rotor device for electric motors comprising at least one or more stator/rotor core assembly(ies) (10.1) stacked one above the other, wherein the stator/rotor core assembly(ies) (10.1) is/are designed as a component formed with rotational symmetry in respect of an axis of rotation (D) having individual laminations (12) arranged stacked one above the other, the individual laminations (12) having a rotationally symmetrical peripheral contour with projections which are arranged at a distance from one another with a predefined spacing in the peripheral direction (U) and which, when stacked one above the other, form pole shoes (14) pointing inwardly or outwardly, which are each wound by an electrically conducting wire with a winding groove (16), each with a groove entrance (17), provided between each of the pole shoes (14), at least the internal peripheral contour of each winding groove (16) and the upper side and lower side of the pole shoe (14) having an electrically insulating, more particularly injection-moulded, plastic layer, characterized in that, when the individual laminations (12)/stator/rotor core assemblies are stacked, at least one continuous flow channel (26.1) running in the longitudinal direction (L) of the stator/rotor device is present in the area of at least one winding groove (16), which is in communication connection with the plastic layer and through which the plastic can be injected/is injected to produce the plastic layer on the inner wall of the winding groove (16).

IPC 8 full level
H02K 1/14 (2006.01); **H02K 1/24** (2006.01); **H02K 15/12** (2006.01)

CPC (source: EP)
H02K 15/12 (2013.01); **H02K 1/146** (2013.01); **H02K 1/24** (2013.01)

Citation (search report)
See references of WO 2019120354A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
DE 202017006523 U1 20180207; DE 112018006510 A5 20201105; EP 3729615 A1 20201028; WO 2019120354 A1 20190627

DOCDB simple family (application)
DE 202017006523 U 20171220; DE 112018006510 T 20181219; DE 2018000375 W 20181219; EP 18845340 A 20181219