

Title (en)
SELF-ALIGNING GEAR PUMP

Title (de)
SELBSTAUSRICHTENDE ZAHNRADPUMPE

Title (fr)
POMPE À ENGRÈNAGE À AUTO-ALIGNEMENT

Publication
EP 3786416 A1 20210303 (EN)

Application
EP 19194371 A 20190829

Priority
EP 19194371 A 20190829

Abstract (en)

Disclosed herein is a gear pump (100) for pumping a fluid (404). The gear pump comprises: a sealed internal chamber (102); a pumping chamber (104) within the sealed internal chamber; a first pump port (122) fluidically connected to the pumping chamber; a second pump port (114) fluidically connected to the pumping chamber; a drive gear (120) within the pumping chamber; an idler gear (122) within the pumping chamber, wherein the drive gear and the idler gear are configured for pumping the fluid between the first pump port and the second pump port; a drive shaft (124) coupled to the drive gear, wherein the drive shaft is configured for rotationally driving the drive gear, wherein the drive shaft is within the sealed internal chamber; an idler shaft (126) coupled to the idler gear, wherein the idler shaft is within the sealed internal chamber, wherein the idler gear is coupled to the idler shaft; a pump housing (106, 108, 110) formed from a first housing element (106), a central housing element (108), and a second housing element (110), wherein the central housing element is positioned between the first housing element and the second housing element, wherein the first housing element, the second housing element and the central housing element form at least a portion of the sealed internal chamber, wherein the pumping chamber is formed entirely within the central housing; a first drive shaft bearing (128), wherein the first drive shaft bearing is mounted partially within the first housing element; a second drive shaft bearing (130), wherein the second drive shaft bearing is mounted partially within the second housing element, wherein the first drive shaft bearing and the second drive shaft bearing both partially extends into and align the drive gear with the pumping chamber; a first idler shaft bearing (132), wherein the first idler shaft bearing is mounted partially within the first housing; a second idler shaft bearing (134), wherein the second idler shaft bearing is mounted partially within the second housing element, wherein the first idler shaft bearing and the second idler shaft bearing both partially extends into the pumping chamber and align the idler gear with the pumping chamber.

IPC 8 full level

F01C 21/02 (2006.01); **F01C 21/10** (2006.01); **F04C 2/18** (2006.01); **F04C 13/00** (2006.01); **F04C 15/00** (2006.01)

CPC (source: EP)

F01C 21/02 (2013.01); **F01C 21/10** (2013.01); **F04C 2/18** (2013.01); **F04C 13/001** (2013.01); **F04C 15/0069** (2013.01); **F04C 2210/1094** (2013.01); **F04C 2240/52** (2013.01); **F05C 2203/0808** (2013.01); **F05C 2203/0817** (2013.01); **F05C 2225/04** (2013.01); **F05C 2225/12** (2013.01)

Citation (applicant)

EP 2282059 A1 20110209 - PULSAFEEDER INC [US]

Citation (search report)

- [I] US 10189005 B2 20190129 - WOLLMANN THOMAS MICHAEL [DE]
- [A] WO 2018114946 A1 20180628 - BOSCH GMBH ROBERT [DE]
- [A] US 2006140793 A1 20060629 - KREBS LARRY F [US]
- [A] JP H08121350 A 19960514 - SHIMADZU CORP
- [A] US 4583924 A 19860422 - ZINGLEIN WOLFGANG [DE], et al

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

EP 3786416 A1 20210303; EP 3786416 B1 20210929; DK 3786416 T3 20211220; ES 2902419 T3 20220328

DOCDB simple family (application)

EP 19194371 A 20190829; DK 19194371 T 20190829; ES 19194371 T 20190829