

Title (en)

A CYLINDER LOCK WITH ENHANCED SECURITY AGAINST BREAK-IN ATTEMPTS

Title (de)

ZYLINDERSCHLOSS MIT ERHÖHTER SICHERHEIT GEGEN EINBRUCHSVERSUCHE

Title (fr)

SERRURE À BARILLET À SÉCURITÉ RENFORCÉE CONTRE LES TENTATIVES D'EFFRACTION

Publication

EP 3802997 A4 20210623 (EN)

Application

EP 18921076 A 20180528

Priority

TR 2018050272 W 20180528

Abstract (en)

[origin: WO2019231411A1] The present invention relates to a cylinder lock (10) comprising: a cylinder plug (30) having a keyway (35) adapted to receive a key; a longitudinally extending first cylinder half (23) and a second cylinder half (24); a rotatable cam (21) co-axial with and connected to the cylinder plug (30) for rotation therewith, the rotatable cam (21) being disposed externally of and between the first second cylinder halves (23, 24); a mechanically weakened cylinder notch (29) provided through at least part of the first cylinder half (23) for forming a breakable tip portion (28); a mechanically weakened plug notch (36) provided through at least part of the cylinder plug (30) for forming a breakable plug portion; a plurality of mutually aligned bores extending at right-angles to the cylinder plug axis and in which housing pins (52) which are substantially of equal length and plug pins (53) which are of different lengths are biased in the direction of the keyway (35) under spring force by a plurality of springs (51). said cylinder lock (10) further comprises at least one retaining pin (32), pre-stressed and displaceable under a spring force, provided at the cylinder plug (30) and depressed by a retaining member (31), said retaining pin (32) adapted to match at least partly with a corresponding retaining recess (27) formed at the first cylinder half (23) such that when the mechanically weakened cylinder notch (29) and plug notch (36) breaks away, said retaining member (31) slides out of the first cylinder half (23) and said retaining pin (32) maintains rest of the cylinder plug (30) in the first cylinder half (23) by matching with the retaining recess (27).

IPC 8 full level

E05B 9/04 (2006.01); **E05B 17/20** (2006.01); **E05B 27/00** (2006.01); **E05B 15/16** (2006.01)

CPC (source: EP)

E05B 9/041 (2013.01); **E05B 15/1614** (2013.01); **E05B 17/0062** (2013.01); **E05B 17/2092** (2013.01)

Citation (search report)

- [A] DE 20021352 U1 20010322 - WINKHAUS FA AUGUST [DE]
- [A] EP 2730727 A2 20140514 - EVVA SICHERHEITSTECHNOLOGIE [AT]
- See references of WO 2019231411A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

WO 2019231411 A1 20191205; EP 3802997 A1 20210414; EP 3802997 A4 20210623

DOCDB simple family (application)

TR 2018050272 W 20180528; EP 18921076 A 20180528