

Title (en)

ROTARY CONTROL QUICK-DISMOUNTING HINGE AND TOILET COVER PLATE HAVING SAME

Title (de)

SCHNELLEDEMONTAGESCHARNIER MIT DREHKONTROLLE UND TOILETTENDECKELPLATTE DAMIT

Title (fr)

CHARNIÈRE À DÉMONTAGE RAPIDE, À COMMANDE ROTATIVE, ET PLAQUE DE COUVERCLE DE TOILETTES COMPRENANT LADITE CHARNIÈRE

Publication

EP 3804594 B1 20231101 (EN)

Application

EP 19784707 A 20190108

Priority

- CN 201810330215 A 20180413
- CN 2019070829 W 20190108

Abstract (en)

[origin: CN108338731A] The invention discloses a rotary control quick-dismounting hinge and a toilet cover plate with the hinge. The rotary control quick-dismounting hinge comprises a support and a rotary shaft, wherein the support is fixed on a ceramic toilet and is provided with a plug pin; the rotary shaft is formed by performing coaxial inserting connection on a fixed shaft and a buffer and is used for a cover plate to perform pivot joint rotation; an upright column is arranged at the radial bottom of the fixed shaft; a pin hole is formed from the bottom surface of the upright column to the fixed shaft; when the plug pin with the height less than the depth of the pin hole is completely inserted into the pin hole to perform positioning, the upright column is pressed on the support; the rotary shaft also comprises a locking device which is arranged on the fixed shaft and is positioned between the buffer and the pin hole; the locking device locks the plug pin and is in linkage cooperation with the cover plate; when the cover plate overturns to a preset angle, the locking device unlocks a lock groove formed in the plug pin, so that the plug pin can be pulled out of the pin hole; when the pressure of the cover plate is completely borne by the support, and the longitudinal connection strength of the upright column and the support is higher; and the locking device is arranged on the fixed shaft between the buffer and a reducing shaft, and overturns to perform linkage locking on the cover plate or unlocks the plug pin, so that the portable dismounting function of the cover plate on the ceramic toilet is realized.

IPC 8 full level

A47K 13/12 (2006.01); **A47K 13/26** (2006.01)

CPC (source: CN EP GB)

A47K 13/12 (2013.01 - CN EP GB); **A47K 13/26** (2013.01 - EP)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

DE 102018120672 A1 20191017; **DE 102018120672 B4 20201231**; CN 108338731 A 20180731; CN 108338731 B 20240607; EP 3804594 A1 20210414; EP 3804594 A4 20210512; EP 3804594 B1 20231101; FR 3080015 A1 20191018; GB 201813899 D0 20181010; GB 2576380 A 20200219; GB 2576380 B 20200812; WO 2019196526 A1 20191017

DOCDB simple family (application)

DE 102018120672 A 20180823; CN 201810330215 A 20180413; CN 2019070829 W 20190108; EP 19784707 A 20190108; FR 1870953 A 20180827; GB 201813899 A 20180828