

Title (en)

PROFILE CYLINDER

Title (de)

PROFILZYLINDER

Title (fr)

CYLINDRE PROFILÉ

Publication

EP 3822432 B1 20240522 (DE)

Application

EP 20205935 A 20201105

Priority

DE 102019130742 A 20191114

Abstract (en)

[origin: CN112796576A] A lock cylinder extending along a longitudinal axis includes: one or more pin-shaped bolts, each pin-shaped bolt having a cylinder pin, a housing pin, and a bolt spring; a housing having a substantially hollow cylindrical core receptacle and a flange portion projecting radially away from the core receptacle with respect to the longitudinal axis, the flange portion being closed on a front side of the housing and open on a rear side or an underside of the housing. In addition, the lock cylinder is provided with a lock cylinder part; the lock cylinder part is rotatably mounted in the cylinder accommodating part of the housing; the lock cylinder includes an inner shell inserted into the flange portion of the housing through an open rear side or lower side.

IPC 8 full level

E05B 9/04 (2006.01); **E05B 9/08** (2006.01); **E05B 9/10** (2006.01); **E05B 17/00** (2006.01); **E05B 27/00** (2006.01)

CPC (source: CN EP)

E05B 9/041 (2013.01 - CN); **E05B 9/042** (2013.01 - CN EP); **E05B 9/045** (2013.01 - EP); **E05B 9/086** (2013.01 - EP); **E05B 9/10** (2013.01 - EP); **E05B 17/0004** (2013.01 - EP); **E05B 27/0014** (2013.01 - CN EP); **E05B 27/0075** (2013.01 - CN); **E05B 27/0092** (2013.01 - CN)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 3822432 A1 20210519; EP 3822432 B1 20240522; EP 3822432 C0 20240522; CN 112796576 A 20210514; DE 102019130742 A1 20210520

DOCDB simple family (application)

EP 20205935 A 20201105; CN 202011277943 A 20201116; DE 102019130742 A 20191114