

Title (en)
ELECTRIC MOTOR COMPRISING A WIRING UNIT AND METHOD FOR PRODUCING AN ELECTRIC MOTOR WITH COMPRISING A WIRING UNIT

Title (de)
ELEKTROMOTOR MIT EINER VERSCHALTUNGSEINHEIT UND VERFAHREN ZUR HERSTELLUNG EINES ELEKTROMOTORS MIT EINER VERSCHALTUNGSEINHEIT

Title (fr)
MOTEUR ÉLECTRIQUE COMPRENANT UNE UNITÉ DE CÂBLAGE ET PROCÉDÉ DE RÉALISATION D'UN MOTEUR ÉLECTRIQUE COMPRENANT UNE UNITÉ DE CÂBLAGE

Publication
EP 3824529 A1 20210526 (DE)

Application
EP 19739198 A 20190704

Priority
• DE 102018005672 A 20180719
• EP 2019025214 W 20190704

Abstract (en)
[origin: WO2020015856A1] The invention relates to an electric motor, in particular a permanent magnet synchronous motor, comprising a rotor arranged such that it can rotate about an axis of rotation and comprising a stator, wherein the stator has multiple coils, wherein each coil has two coil connections, in particular wherein the stator has multiple stator segments and each stator segment has exactly one coil, wherein the coils are wired to one another by means of a wiring unit, in particular in a star connection, wherein the wiring unit comprises a carrier part, in particular a substantially annular carrier part, in particular a carrier part formed by an insulating material, for receiving multiple, in particular at least four, spaced-apart wiring elements, in particular wherein the wiring unit is arranged at an axial end of the stator, in particular concentrically to the axis of rotation, wherein, in particular at least three, first wiring elements are provided, wherein each of the first wiring elements has two, in particular exactly two, spaced-apart contacting regions and a connection region connected to the contacting regions, in particular such that the connection region is arranged between the contacting regions, wherein the contacting regions, in particular all the contacting regions, of each first wiring element are each connected to one of the coil connections at a respective connection point, in particular electrically connected, in particular integrally connected by means of laser welding, wherein the region covered by the connection region of one of the first wiring elements in the circumferential and radial direction overlaps with a respective region covered by the connection region of another of the first wiring elements in the circumferential and radial direction, wherein the regions covered by the connection regions of the first wiring elements in the axial direction are the same and the regions covered by the connection regions of the first wiring elements in the radial direction are the same.

IPC 8 full level
H02K 3/52 (2006.01)

CPC (source: EP US)
H02K 3/522 (2013.01 - EP US); **H02K 15/0062** (2013.01 - US); **H02K 21/16** (2013.01 - US); **H02K 2203/09** (2013.01 - EP US)

Citation (search report)
See references of WO 2020015856A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
WO 2020015856 A1 20200123; CN 112425042 A 20210226; DE 102019004590 A1 20200123; EP 3824529 A1 20210526; US 2021273516 A1 20210902

DOCDB simple family (application)
EP 2019025214 W 20190704; CN 201980047855 A 20190704; DE 102019004590 A 20190704; EP 19739198 A 20190704; US 201917261258 A 20190704