

Title (en)  
LOAD-BREAK SWITCH WITHOUT SF6 GAS HAVING A VACUUM CIRCUIT INTERRUPTER FOR MEDIUM-VOLTAGE SWITCHING SYSTEMS

Title (de)  
LASTTRENNSCHALTER OHNE SF6-GAS MIT EINEM VAKUUMLEISTUNGSSCHALTER FÜR MITTELSPANNUNGSSCHALTANLAGEN

Title (fr)  
INTERRUPTEUR COUPE-CHARGE SANS GAZ SF6 DOTÉ D'UN INTERRUPTEUR DE CIRCUIT À VIDE POUR SYSTÈMES DE COMMUTATION MOYENNE TENSION

Publication  
**EP 3843117 A1 20210630 (EN)**

Application  
**EP 19020727 A 20191224**

Priority  
EP 19020727 A 20191224

Abstract (en)  
The present invention relates to a load-break switch (1) having a vacuum circuit interrupter (4) for medium-voltage switching systems. The load-break switch (1) comprises an inner elongated insulating housing (9) enclosing a vacuum interrupter (4) comprising a vacuum chamber (13) containing a fixed contact (20) electrically interconnected with a second conductive bar (16) and a movable contact (21) electrically connected to a flexible conductor (14) and a first switch contact (17), a second switch contact (18) electrically connected with a first conductive bar (15), a pair of parallelly arranged rotatable blades (26), wherein the pair of rotatable blades (26) is movable by a drive shaft (27) between a main current path in electrical communication with the fixed contact (20) and an isolation path when the movable contact (21) is spaced apart from the fixed contact (20), said pair of rotatable blades (26) being connected to a pair of parallelly arranged cam plates (25) enabling formation of the isolation path in the event of an extinguished arc or the main current path, said drive shaft (27) in combination with said cam plates (25) on one side, causes said pair of rotatable blades (26) to acquire said main current path and, on another side, to acquire the isolation path. One end of each of the rotatable blades (26) is in electrical contact with the first switch contact (17) and an opposite end of each rotatable blades (26) is in electrical contact with the second switch contact (18), wherein the main current path is formed in a first position of the pair of rotatable blades (26) and an isolation path is formed in a second position of the pair of rotatable blades (26), the pair of rotatable blades (26) is embodied as rotatable by 90° around the drive shaft (27).

IPC 8 full level  
**H01H 33/12** (2006.01); **H01H 33/02** (2006.01)

CPC (source: EP)  
**H01H 33/022** (2013.01); **H01H 33/122** (2013.01); **H01H 3/42** (2013.01); **H01H 33/42** (2013.01); **H01H 33/6661** (2013.01)

Citation (applicant)  
• EP 0342603 A2 19891123 - TOSHIBA KK [JP]  
• EP 0433184 A1 19910619 - MERLIN GERIN [FR]  
• EP 0542637 B1 19970723 - SCHNEIDER ELECTRIC SA [FR]  
• EP 2789000 B1 20180103 - SIEMENS AG [DE]

Citation (search report)  
• [Y] EP 3367408 A1 20180829 - TOSI GIAMPIETRO [IT]  
• [Y] WO 2011161121 A1 20111229 - IPT INTERNAT POWER & TECHNOLOGY GMBH [DE], et al  
• [Y] WO 2011147717 A1 20111201 - SIEMENS AG [DE], et al  
• [Y] WO 2012171569 A1 20121220 - ABB TECHNOLOGY AG [CH], et al  
• [Y] CN 106953264 A 20170714 - ZHUHAI AEROSPACE SCIENCE & TECH INNOVATION INDUSTRIAL CO LTD  
• [Y] US 5834725 A 19981110 - CLARKE ROY [GB], et al  
• [Y] CN 109637888 A 20190416 - JIANGSU DAYBRIGHT INTELLIGENT ELECTRIC CO LTD

Cited by  
SE2251161A1; SE545785C2

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)  
BA ME

DOCDB simple family (publication)  
**EP 3843117 A1 20210630; EP 3843117 B1 20231115; EP 3843117 C0 20231115**

DOCDB simple family (application)  
**EP 19020727 A 20191224**