

Title (en)

COMPOSITION AND METHOD FOR PREVENTING OR REDUCING LOW SPEED PRE-IGNITION IN SPARK-IGNITED INTERNAL COMBUSTION ENGINES

Title (de)

ZUSAMMENSETZUNG UND VERFAHREN ZUR VERHINDERUNG ODER VERMINDERUNG DER NIEDRIGGESCHWINDIGKEITSVORZÜNDUNG BEI OTTOMOTOREN

Title (fr)

COMPOSITION ET PROCÉDÉ POUR EMPÊCHER OU RÉDUIRE LE PRÉ-ALLUMAGE À FAIBLE VITESSE DANS DES MOTEURS À COMBUSTION INTERNE À ALLUMAGE PAR ÉTINCELLES

Publication

EP 3880771 A1 20210922 (EN)

Application

EP 19778690 A 20190923

Priority

- US 201862767686 P 20181115
- US 201916362157 A 20190322
- IB 2019058057 W 20190923

Abstract (en)

[origin: CN113227332A] Disclosed herein is a fuel composition having (1) greater than 50 wt % of a hydrocarbon fuel boiling in the gasoline or diesel range and (2) a minor amount of a low-speed pre-ignition (LSPI)-reducing additive having one or more of an amidine, or a beta-amino alkanol having the structure [Formula see description], wherein R1, R2, R3, and R4 are each independently selected from hydrogen, aromatic ring, and a C1-C20 alkyl group and R5 is hydrogen or an alcohol having the structure -(CH)R6-OH. R6 is hydrogen, a C1-C10 alkyl group, or a C1-C10 alkenyl group, or a salt thereof.

IPC 8 full level

C10L 1/22 (2006.01); C10L 1/224 (2006.01); C10M 133/02 (2006.01)

CPC (source: EP)

C10L 1/2225 (2013.01); C10L 1/224 (2013.01); C10L 1/183 (2013.01); C10L 1/1857 (2013.01); C10L 1/2222 (2013.01); C10L 1/223 (2013.01); C10L 1/2235 (2013.01); C10L 1/2283 (2013.01); C10L 1/232 (2013.01); C10L 1/233 (2013.01); C10L 10/10 (2013.01); C10L 2200/0423 (2013.01); C10L 2270/023 (2013.01)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

CN 113227332 A 20210806; CN 113227332 B 20240112; EP 3880771 A1 20210922

DOCDB simple family (application)

CN 201980085825 A 20190923; EP 19778690 A 20190923