

Title (en)  
CROSSLINKABLE POLYMER COMPOSITION CONSISTING OF TWO COPOLYMERISATES, WHICH ARE REACTIVE WITH EACH OTHER AND HAVE DIFFERENT GLASS TRANSITION TEMPERATURES

Title (de)  
VERNETZBARE POLYMERZUSAMMENSETZUNG AUS ZWEI MITEINANDER REAKTIVEN COPOLYMERISATEN UNTERSCHIEDLICHER GLASSÜBERGANGSTEMPERATUREN

Title (fr)  
COMPOSITION POLYMÈRE RÉTICULABLE COMPOSÉE DE DEUX COPOLYMÈRES RÉAGISSANT L'UN AVEC L'AUTRE PRÉSENTANT DES TEMPÉRATURE DE TRANSITION VITREUSE DIFFÉRENTES

Publication  
**EP 3887464 A1 20211006 (DE)**

Application  
**EP 18808006 A 20181126**

Priority  
EP 2018082506 W 20181126

Abstract (en)  
[origin: WO2020108723A1] The invention relates to a crosslinkable polymer composition in the form of an aqueous polymer dispersion or a polymer powder, containing A) a mixed polymerisate of one or more comonomers a1) from the group containing vinyl esters of unbranched or branched alkyl carboxylic acids with 1 to 18 C atoms, acrylic acid esters, and methacrylic acid esters of branched or unbranched alcohols with 1 to 15 C atoms, dienes, olefins, vinyl aromatics, and vinyl halides, and 0.1 to 30 wt.%, based on the total weight of the comonomers, of one or more ethylenically unsaturated functional comonomers a2, which contain carboxyl, hydroxy, or NH groups, and B) a mixed polymerisate of one or more comonomers b1) from the group containing vinyl ester or unbranched or branched alkyl carboxylic acids with 1 to 18 C atoms, acrylic acid esters, and methacrylic acid esters of branched or unbranched alcohols with 1 to 15 C atoms, dienes, olefins, vinyl aromatics, and vinyl halides, and 0.1 to 30 wt.%, based on the total weight of the comonomers, of one or more ethylenically unsaturated functional comonomers b2) which can react with the functional groups of the comonomers a2 ) and which contain epoxy, N-methylol, or isocyanate groups. The invention is characterized in that one of the mixed polymerisates A) or B) has a glass transition temperature Tg of less than 30 °C and the respective other mixed polymerisate A) or B) has a glass transition temperature Tg of more than 50 °C.

IPC 8 full level  
**C09D 125/10** (2006.01); **B27N 3/00** (2006.01); **C09D 5/03** (2006.01); **C09D 125/14** (2006.01); **C09D 133/12** (2006.01); **C09D 133/14** (2006.01); **E04C 2/16** (2006.01)

CPC (source: EP)  
**B27N 3/002** (2013.01); **B27N 3/04** (2013.01); **C09D 5/03** (2013.01); **C09D 125/10** (2013.01); **C09D 125/14** (2013.01); **C09D 133/12** (2013.01); **C09D 133/14** (2013.01); **B27N 3/28** (2013.01); **C08L 2205/025** (2013.01); **C09D 131/04** (2013.01)

Citation (search report)  
See references of WO 2020108723A1

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)  
BA ME

DOCDB simple family (publication)  
**WO 2020108723 A1 20200604**; EP 3887464 A1 20211006

DOCDB simple family (application)  
**EP 2018082506 W 20181126**; EP 18808006 A 20181126