

Title (en)
RELAY

Title (de)
RELAIS

Title (fr)
RELAIS

Publication
EP 3929958 A4 20221123 (EN)

Application
EP 20759207 A 20200212

Priority
• JP 2019028888 A 20190220
• JP 2020005226 W 20200212

Abstract (en)
[origin: EP3929958A1] An appropriate insulation distance for a movable contact piece is secured while suppressing enlargement of a relay. An insulating member is connected to a first movable contact piece. A movable iron core is connected to the insulating member. The first movable contact piece and the movable iron core are electrically insulated by the insulating member.

IPC 8 full level
H01H 50/02 (2006.01); **H01H 50/20** (2006.01); **H01H 50/64** (2006.01)

CPC (source: EP US)
H01H 50/02 (2013.01 - US); **H01H 50/026** (2013.01 - EP); **H01H 50/20** (2013.01 - US); **H01H 50/44** (2013.01 - US); **H01H 50/546** (2013.01 - US);
H01H 50/58 (2013.01 - US); **H01H 50/64** (2013.01 - US); **H01H 50/648** (2013.01 - EP); **H01H 51/065** (2013.01 - US); **H01H 50/546** (2013.01 - EP);
H01H 2050/446 (2013.01 - US)

Citation (search report)
• [XY] US 2016300680 A1 20161013 - YOKOYAMA KOJI [JP], et al
• [X] US 6975194 B2 20051213 - NISHIDA TAKESHI [JP], et al
• [Y] JP S56112829 U 19810831
• [Y] JP S4322993 Y1 19680928
• [Y] ES 2606317 T3 20170323 - OMRON TATEISI ELECTRONICS CO [JP]
• See also references of WO 2020170895A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 3929958 A1 20211229; EP 3929958 A4 20221123; CN 113412528 A 20210917; JP 2020136102 A 20200831; JP 7088074 B2 20220621;
TW 202032605 A 20200901; TW I750587 B 20211221; US 2022108860 A1 20220407; WO 2020170895 A1 20200827

DOCDB simple family (application)
EP 20759207 A 20200212; CN 202080012519 A 20200212; JP 2019028888 A 20190220; JP 2020005226 W 20200212;
TW 109104614 A 20200214; US 202017429628 A 20200212