

Title (en)

HYBRID MODULE HAVING A SEPARATING CLUTCH AND ACTUATION UNIT WITHOUT COMPENSATION, AND DRIVE TRAIN

Title (de)

HYBRIDMODUL MIT TRENNKUPPLUNG UND BETÄTIGUNGSEINHEIT OHNE KOMPENSATION; SOWIE ANTRIEBSSTRANG

Title (fr)

MODULE HYBRIDE AVEC EMBRAYAGE DE COUPURE ET UNITÉ D'ACTIONNEMENT SANS COMPENSATION ; AINSI QUE CHAÎNE CINÉMATIQUE

Publication

EP 3934927 A1 20220112 (DE)

Application

EP 20705882 A 20200120

Priority

- DE 102019105789 A 20190307
- DE 2020100035 W 20200120

Abstract (en)

[origin: WO2020177798A1] The invention relates to a hybrid module (1) for a drive train (2) of a motor vehicle, comprising a housing (3), an input shaft (4) which can be rotated relative to the housing (3) and can be connected to an internal combustion engine, an electric machine (5), a carrier (7) rotationally coupled to a rotor (6) of the electric machine (5), a separating clutch (8) operatively introduced between the input shaft (4) and the carrier (7), and a hydraulic actuation unit (9) designed for adjusting the separating clutch (8) between a closed position and an open position, wherein the actuation unit (9) has a sliding element (11) shiftingly acting on multiple friction elements (10a, 10b) of the separating clutch (8), which sliding element (11) encloses a hydraulic pressure chamber (13) towards its first axial side (12a) together with the carrier (7) and is applied with an axial restoring force towards its second axial side (12b) by a restoring spring unit (14), wherein the restoring spring unit (14) and the pressure chamber (13) are designed and coordinated in such a way that, during operation of the hybrid module (1), with the carrier (7) rotating up to a rotational speed of at least 3000 U/min, the restoring force generated by the restoring spring unit (14) is greater than an axial adjustment force of the pressure chamber (13) generated by a centrifugal force in the pressure chamber (13) and acting axially opposite the restoring force, on the sliding element (11) in the direction of the closed position. The invention also relates to a drive train (2) comprising said hybrid module (1).

IPC 8 full level

B60K 6/387 (2007.10); **B60K 6/40** (2007.10); **B60K 6/48** (2007.10); **B60K 6/547** (2007.10); **F16D 13/38** (2006.01); **F16D 13/44** (2006.01); **F16D 13/52** (2006.01); **F16D 21/02** (2006.01); **F16D 21/06** (2006.01); **F16D 25/04** (2006.01); **F16D 25/0638** (2006.01); **F16D 43/284** (2006.01)

CPC (source: EP US)

B60K 6/387 (2013.01 - EP US); **B60K 6/40** (2013.01 - EP); **B60K 6/48** (2013.01 - EP); **F15B 15/20** (2013.01 - US); **F16D 25/0638** (2013.01 - EP); **F16D 25/10** (2013.01 - EP); **B60K 2006/4825** (2013.01 - EP); **F16D 43/284** (2013.01 - EP); **F16D 2021/0661** (2013.01 - EP); **F16D 2021/0692** (2013.01 - EP); **Y02T 10/62** (2013.01 - EP)

Citation (search report)

See references of WO 2020177798A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

DE 102019115904 A1 20200910; CN 113543997 A 20211022; EP 3934927 A1 20220112; US 2022185091 A1 20220616; WO 2020177798 A1 20200910

DOCDB simple family (application)

DE 102019115904 A 20190612; CN 202080017571 A 20200120; DE 2020100035 W 20200120; EP 20705882 A 20200120; US 202017432157 A 20200910