

## Title (en)

HEAT EXCHANGER ASSEMBLY HAVING AT LEAST ONE MULTI-PASS HEAT EXCHANGER AND METHOD FOR OPERATING A HEAT EXCHANGER ASSEMBLY

## Title (de)

WÄRMEÜBERTRAGERANORDNUNG MIT WENIGSTENS EINEM MEHRPASS-WÄRMEÜBERTRAGER UND VERFAHREN ZUM BETRIEB EINER WÄRMEÜBERTRAGERANORDNUNG

## Title (fr)

ENSEMBLE ÉCHANGEUR DE CHALEUR COMPRENANT AU MOINS UN ÉCHANGEUR DE CHALEUR À PLUSIEURS PASSAGES ET PROCÉDÉ POUR FAIRE FONCTIONNER UN ENSEMBLE ÉCHANGEUR DE CHALEUR

## Publication

**EP 3953652 A1 20220216 (DE)**

## Application

**EP 20714971 A 20200323**

## Priority

- DE 102019110236 A 20190418
- EP 2020057986 W 20200323

## Abstract (en)

[origin: WO2020212090A1] The invention relates to a heat exchanger assembly with at least one multi-pass heat exchanger, comprising a first distributor (1) with a first connection part (1a) for connecting to a fluid line (9), a second distributor (2) with a second connection part (2a) for connecting to a fluid line (9), and at least one first deflection distributor (4), as well as a plurality of tube lines (5) through which a fluid, in particular water, can flow, wherein the first distributor (1) and the second distributor (2) are arranged at one end (A) of the heat exchanger assembly, the deflection distributor (4) is arranged at the opposite end (B) and the tube lines (5) extend from the one end (A) to the opposite end (B), and wherein the first connection part (1a) is arranged at a lowest point (T) or at least near to the lowest point (T) of the first distributor (1) and the second connection piece (2a) is arranged at a lowest point (T) or at least near to the lowest point (T) of the second distributor (2). In order to allow for the heat exchanger assembly to be quickly filled with the fluid and quickly emptied, a third connection part (3) is arranged on the first distributor (1) and/or on the second distributor (2) at a highest point (H) or at least near to the highest point (H) of the respective distributor (1 or 2), and at least one ventilation opening (10) is provided at a highest point (T) or at least near to the highest point (T) of the deflection distributor (4) for pressure equalisation with the environment.

## IPC 8 full level

**F28D 1/04** (2006.01); **F28B 1/06** (2006.01); **F28D 1/02** (2006.01); **F28D 1/053** (2006.01); **F28F 9/02** (2006.01); **F28F 27/00** (2006.01)

## CPC (source: CN EP US)

**F28B 1/06** (2013.01 - EP); **F28D 1/0233** (2013.01 - US); **F28D 1/024** (2013.01 - EP); **F28D 1/0417** (2013.01 - US); **F28D 1/0426** (2013.01 - EP US); **F28D 1/0435** (2013.01 - EP); **F28D 1/0443** (2013.01 - US); **F28D 1/05325** (2013.01 - EP US); **F28D 1/05333** (2013.01 - EP US); **F28D 1/05366** (2013.01 - EP US); **F28D 7/0066** (2013.01 - CN); **F28F 9/0243** (2013.01 - EP); **F28F 9/22** (2013.01 - CN); **F28F 9/26** (2013.01 - CN); **F28F 27/00** (2013.01 - CN EP); **F28F 27/02** (2013.01 - US); **F28D 2001/0266** (2013.01 - EP); **F28F 2009/222** (2013.01 - CN); **F28F 2265/06** (2013.01 - EP); **F28F 2265/18** (2013.01 - EP); **Y02B 30/56** (2013.01 - EP)

## Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

## Designated extension state (EPC)

BA ME

## DOCDB simple family (publication)

**WO 2020212090 A1 20201022**; CA 3134930 A1 20201022; CN 113710981 A 20211126; CN 113710981 B 20230912; CN 117722883 A 20240319; DE 102019110236 A1 20201022; EP 3953652 A1 20220216; EP 3953652 B1 20230607; EP 3953652 C0 20230607; EP 3988881 A1 20220427; EP 3988881 B1 20230705; EP 3988881 C0 20230705; US 11976883 B2 20240507; US 2022136776 A1 20220505; US 2022205724 A1 20220630

## DOCDB simple family (application)

**EP 2020057986 W 20200323**; CA 3134930 A 20200323; CN 202080029427 A 20200323; CN 202310629418 A 20200323; DE 102019110236 A 20190418; EP 20714971 A 20200323; EP 21202046 A 20200323; US 202017601793 A 20200323; US 202117502231 A 20211015