

Title (en)
LIDAR SENSOR FOR OPTICALLY DETECTING A FIELD OF VIEW AND METHOD FOR DRIVING A LIDAR SENSOR

Title (de)
LIDAR-SENSOR ZUR OPTISCHEN ERFASSUNG EINES SICHTFELDES UND VERFAHREN ZUR ANSTEUERUNG EINES LIDAR-SENSORS

Title (fr)
CAPTEUR LIDAR POUR L'ENREGISTREMENT OPTIQUE D'UN CHAMP DE VISION ET PROCÉDÉ POUR LA COMMANDE DU CAPTEUR LIDAR

Publication
EP 3953735 A1 20220216 (DE)

Application
EP 20712938 A 20200319

Priority
• DE 102019205243 A 20190411
• EP 2020057613 W 20200319

Abstract (en)
[origin: WO2020207740A1] A LIDAR sensor (100) for optically detecting a field of view, comprising a transmitter unit with at least one light source (101, 101-1, 101-2) for generating and outputting primary light into a first angular range (111) of the field of view; a deflection unit (105), which is rotatable and/or swivelable about an axis of rotation (106), for deflecting primary light incident on the deflection unit (105) into a second angular range (505) of the field of view; and a receiver unit (110) with at least one detector unit (204) for receiving secondary light, which was reflected and/or scattered by an object in the field of view; wherein the first angular range (111) extends in a plane disposed parallel to the axis of rotation (106) of the deflection unit (105); and wherein the transmitter unit is embodied to output the primary light as a first transmission beam (102-1) with two marginal rays (103-1, 103-2) and as at least one second transmission beam (102-2) with two marginal rays (104-1, 104-2) into at least two portions (111-1, 111-2) of the first angular range (111); and wherein the transmitter unit is furthermore embodied to output the first transmission beam (102-1) in such a way that the first marginal ray (103-1) of the first transmission beam (102-1) is incident on a first edge region (112-1) of a surface of the deflection unit (105); and to output at least one second transmission beam (102-2) in such a way that the first marginal ray (104-1) of this second transmission beam (102-2) is incident on a second edge region (112-2) of the surface of the deflection region (105) lying opposite the first edge region.

IPC 8 full level
G01S 17/931 (2020.01); **G01S 7/481** (2006.01)

CPC (source: EP KR US)
G01S 7/4814 (2013.01 - EP); **G01S 7/4815** (2013.01 - EP KR US); **G01S 7/4817** (2013.01 - EP KR US); **G01S 17/931** (2020.01 - EP KR US)

Citation (search report)
See references of WO 2020207740A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
WO 2020207740 A1 20201015; CN 113966477 A 20220121; DE 102019205243 A1 20201015; EP 3953735 A1 20220216; JP 2022526638 A 20220525; JP 7377885 B2 20231110; KR 20210151884 A 20211214; US 2022155424 A1 20220519

DOCDB simple family (application)
EP 2020057613 W 20200319; CN 202080042723 A 20200319; DE 102019205243 A 20190411; EP 20712938 A 20200319; JP 2021559722 A 20200319; KR 20217036394 A 20200319; US 202017594194 A 20200319