

Title (en)  
ADAPTABLE INSULATING GLAZING UNIT (VARIANTS)

Title (de)  
ANPASSBARE ISOLIERVERGLASUNGSEINHEIT (VARIANTEN)

Title (fr)  
ENSEMBLE DE VITRAGE ISOLANT ADAPTATIF (VARIANTES)

Publication  
**EP 3954854 A4 20220706 (DE)**

Application  
**EP 19936177 A 20190708**

Priority  
• RU 2019120384 A 20190701  
• RU 2019000485 W 20190708

Abstract (en)  
[origin: RU2708215C1] FIELD: construction.SUBSTANCE: invention relates to construction, in particular to insulating glass unit, intended for use instead of opening flaps of windows and doors, without using flap profiles, in which standard insulating glazing units or insulating glass units with one protruding outer glass are usually fixed. Adaptive insulating glazing unit is intended for use on windows and doors already installed in opening or facade, is also intended for use in production of new windows and doors, which, in turn, are used for glazing openings of doors and windows (blind glazing or with opening flap inside, sideways, outside or upwards from frame) in apartment houses, in public and industrial buildings, display cases. Adaptive insulating glass unit intended for use in place of opening flaps of windows and doors, without using flap profiles, in which standard insulating glazing units or insulating glazing units with one protruding outer glass are usually fixed, extends the possibilities for designing new window and door systems. Adaptive insulating glass unit comprises two outer glass and at least one inner glass spaced apart by means of spacers placed between the glass. At that, the outer glass is always larger than the inner ones, and the profile is inserted between them against all internal glass and simultaneously to one of the external glasses and is glued to this outer glass by means of a rigid adhesive with additional fixation of the bonded profile by using the spacer element to the other outer glass, with filling with elastic glue of sealant formed gap between profile and that external glass, to which profile is not glued with rigid glue, outer part of profile is made with possibility of fixing parts of fittings and seals, adapting adaptive insulating glass unit to specific window systems.EFFECT: increased speed and accuracy of assembling multi-chamber insulating double-glazed windows with a glued profile, as well as high light transmission, high heat-insulating and sound-insulating properties of already developed window and door systems without the need to reconfigure production processes, without the need for readjustment and replacement of equipment used in production of windows, high light transmission, high heat-insulating and sound-insulating properties already installed in openings and facades of buildings of window and door systems without the need for their re-installation.12 cl, 6 dwg

IPC 8 full level  
**E06B 3/02** (2006.01); **E06B 3/32** (2006.01); **E06B 3/66** (2006.01)

CPC (source: EP RU US)  
**E06B 3/025** (2013.01 - EP); **E06B 3/325** (2013.01 - EP); **E06B 3/56** (2013.01 - RU); **E06B 3/64** (2013.01 - RU); **E06B 3/6617** (2013.01 - EP US); **E06B 3/66342** (2013.01 - US); **E06B 3/66361** (2013.01 - US); **E06B 3/66366** (2013.01 - US); **E06B 3/673** (2013.01 - RU); **E06B 2003/6638** (2013.01 - US); **E06B 2003/66385** (2013.01 - US)

Citation (search report)  
• [XAI] EP 2436865 A1 20120404 - INLES D D [SI]  
• [A] EP 3002402 A1 20160406 - AGC GLASS EUROPE [BE]  
• [A] EP 1528213 A1 20050504 - PIAVEVETRO S R L [IT]  
• [A] EP 2672051 A1 20131211 - UNIFORM S P A [IT]  
• See references of WO 2021002768A1

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)  
BA ME

DOCDB simple family (publication)  
**EP 3954854 A1 20220216; EP 3954854 A4 20220706**; RU 2708215 C1 20191204; US 2022186549 A1 20220616; WO 2021002768 A1 20210107

DOCDB simple family (application)  
**EP 19936177 A 20190708**; RU 2019000485 W 20190708; RU 2019120384 A 20190701; US 201917605178 A 20190708