

Title (en)

METHOD FOR STERILIZING BEVERAGE FILLING DEVICE AND BEVERAGE FILLING DEVICE

Title (de)

VERFAHREN ZUM STERILISIEREN EINER GETRÄNKEABFÜLLVORRICHTUNG UND GETRÄNKEABFÜLLVORRICHTUNG

Title (fr)

PROCÉDÉ DE STÉRILISATION DE DISPOSITIF DE REMPLISSAGE DE BOISSON, ET DISPOSITIF DE REMPLISSAGE DE BOISSON

Publication

**EP 3957598 A1 20220223 (EN)**

Application

**EP 20791223 A 20200413**

Priority

- JP 2019078831 A 20190417
- JP 2020016344 W 20200413

Abstract (en)

To reduce the time required to start a drink filling operation or the time interval between productions. In a method of sterilizing a drink filling apparatus that includes drink supply piping that feeds a drink into a filling machine through a heating sterilization part, a heated liquid or heated steam is fed to the drink supply piping, temperatures of the drink supply piping at a plurality of positions are detected at predetermined time intervals, a lowest temperature is selected from the detected temperatures, an F value is calculated for the selected lowest temperature, the calculated F value is integrated, and a sterilization step is ended when the integrated F value reaches a target value.

IPC 8 full level

**B67C 3/00** (2006.01); **A61L 2/04** (2006.01); **A61L 2/07** (2006.01); **B08B 9/032** (2006.01)

CPC (source: EP US)

**A61L 2/04** (2013.01 - EP); **A61L 2/07** (2013.01 - EP US); **A61L 2/186** (2013.01 - EP); **B08B 9/027** (2013.01 - EP);  
**B08B 9/0325** (2013.01 - EP US); **A61L 2202/11** (2013.01 - EP); **A61L 2202/14** (2013.01 - EP); **B08B 2230/01** (2013.01 - EP US);  
**B67C 3/001** (2013.01 - EP)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

**EP 3957598 A1 20220223; EP 3957598 A4 20231025;** CN 113614020 A 20211105; CN 113614020 B 20230523; JP 2020175919 A 20201029;  
JP 6761507 B1 20200923; US 2022226516 A1 20220721; WO 2020213575 A1 20201022

DOCDB simple family (application)

**EP 20791223 A 20200413;** CN 202080023650 A 20200413; JP 2019078831 A 20190417; JP 2020016344 W 20200413;  
US 202017593068 A 20200413