

Title (en)  
THREE-WHEELED ELECTRIC VEHICLE ACCORDING TO THE EU VEHICLE CLASS L2E-U

Title (de)  
DREIRÄDRIGES ELEKTROFAHRZEUG NACH EG-FAHRZEUGKLASSE L2E-U

Title (fr)  
VÉHICULE ÉLECTRIQUE À TROIS ROUES SELON LA CLASSE DE VÉHICULE L2E-U DE L'UE

Publication  
**EP 3962762 A2 20220309 (DE)**

Application  
**EP 20732100 A 20200430**

Priority  
• DE 102019003129 A 20190502  
• EP 2020000100 W 20200430

Abstract (en)  
[origin: WO2020221474A2] The invention relates to a three-wheeled electric vehicle according to the EU vehicle class L2e-U which has two rear wheels (100 and 100') which are driven electromotively and are each driven by a wheel hub motor which is embodied as a multi-phase synchronous motor with an integrated motor controller and is configured for a maximum continuous rated power of greater than 2 kW and less than 6 kW, in particular for a maximum continuous rated power of approximately 4 kW. A telescopic spring fork (80) is pivotably coupled to the front end of the vehicle bodywork (3) and is capable of executing, with respect to the longitudinal direction of the vehicle, a maximum steering angle lock of approximately minus 80° up to approximately plus 80°, which is sensed by a steering angle sensor which generates a corresponding steering angle signal. In addition, a controller which is equipped with a data storage capacity and digital data processing capacity and which actuates the two motor controllers in such a way that when cornering occurs the two drive wheels (100 and 100') are each operated with a different torque is mounted on the vehicle (2). For example, the controller can bring about a starting and obstacle-overcoming mode which is executed at a vehicle speed of 0 to 2 km/h, wherein, at a large steering angle lock of up to 80°, the motor which is mounted on the wheel on the outside of the bend supplies approximately 90% of the total torque which is requested with the given acceleration rotational engagement position and the motor which is mounted on the wheel on the inside of the bend supplies approximately 10% of the total requested torque, that is to say a torque ratio of 90 to 10 is set. When there is a smaller steering lock, a proportionally correspondingly reduced torque ratio is set until such a torque ratio of 50 to 50 is reached for straight ahead travel.

IPC 8 full level  
**B60K 7/00** (2006.01); **B60L 7/24** (2006.01); **B60L 15/20** (2006.01); **B60L 15/32** (2006.01); **B60L 50/51** (2019.01); **B62D 23/00** (2006.01); **B62D 61/08** (2006.01); **B62K 5/027** (2013.01); **B62K 5/06** (2006.01); **B62K 7/00** (2006.01); **B62K 25/04** (2006.01)

CPC (source: EP)  
**B60K 7/0007** (2013.01); **B60L 7/24** (2013.01); **B60L 15/2036** (2013.01); **B60L 50/51** (2019.01); **B62D 23/005** (2013.01); **B62D 61/08** (2013.01); **B62K 5/027** (2013.01); **B62K 5/06** (2013.01); **B62K 7/00** (2013.01); **B62K 25/04** (2013.01); **B60K 2007/0092** (2013.01); **B60L 2200/22** (2013.01); **B60L 2220/14** (2013.01); **B60L 2220/44** (2013.01); **B60L 2240/24** (2013.01); **B60L 2240/423** (2013.01); **B60L 2240/463** (2013.01); **B60L 2250/24** (2013.01); **B60L 2250/28** (2013.01); **B60L 2260/22** (2013.01); **B60Y 2200/12** (2013.01); **B60Y 2200/122** (2013.01); **B62K 2204/00** (2013.01); **Y02T 10/64** (2013.01); **Y02T 10/70** (2013.01); **Y02T 10/72** (2013.01)

Citation (search report)  
See references of WO 2020221474A2

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)  
BA ME

DOCDB simple family (publication)  
**DE 102019003129 B3 20200625**; EP 3962762 A2 20220309; WO 2020221474 A2 20201105; WO 2020221474 A3 20210128; WO 2020221474 A9 20210325

DOCDB simple family (application)  
**DE 102019003129 A 20190502**; EP 2020000100 W 20200430; EP 20732100 A 20200430