

Title (en)

METHOD AND DEVICE FOR DETERMINING SLOSHING

Title (de)

VERFAHREN UND VORRICHTUNG ZUR BESTIMMUNG VON SLOSHING

Title (fr)

MÉTHODE ET DISPOSITIF DE DÉTERMINATION DU BALLOTTEMENT

Publication

EP 3966101 A1 20220316 (FR)

Application

EP 20723138 A 20200507

Priority

- FR 1904837 A 20190509
- EP 2020062678 W 20200507

Abstract (en)

[origin: WO2020225353A1] The invention relates to a method (200) for determining the sloshing of a liquid load of a ship, the method (200) comprising: a step (206) of determining a single-mode excitation on the basis of a multi-mode excitation to which the vessel is subjected, the multi-mode excitation comprising a wave state and a sea state of the wind, wherein the wave state comprises a wave direction and the sea state of the wind comprises a sea direction of the wind, and wherein the single-mode excitation has a total direction equivalent to either the wave direction or the sea direction of the wind closest to a direction perpendicular to the longitudinal axis of the ship, and a step (208) of determining a datum relating to the sloshing of the load on the basis of the single-mode excitation.

IPC 8 full level

B63B 25/24 (2006.01)

CPC (source: EP US)

B63B 25/24 (2013.01 - EP US); **B63B 79/20** (2020.01 - US)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

WO 2020225353 A1 20201112; AU 2020269409 A1 20211118; BR 112021022113 A2 20220104; CN 113795422 A 20211214; CN 113795422 B 20240611; EP 3966101 A1 20220316; EP 3966101 B1 20221214; ES 2939288 T3 20230420; FR 3095802 A1 20201113; FR 3095802 B1 20230324; SG 11202112068U A 20211129; US 11987327 B2 20240521; US 2022204141 A1 20220630

DOCDB simple family (application)

EP 2020062678 W 20200507; AU 2020269409 A 20200507; BR 112021022113 A 20200507; CN 202080034422 A 20200507; EP 20723138 A 20200507; ES 20723138 T 20200507; FR 1904837 A 20190509; SG 11202112068U A 20200507; US 202017607321 A 20200507