

Title (en)
HOUSEHOLD DISHWASHING MACHINE

Title (de)
HAUSHALTGESCHIRRSPÜLMASCHINE

Title (fr)
LAVE-VAISSELLE DOMESTIQUE

Publication
EP 3998009 A1 20220518 (EN)

Application
EP 21210074 A 20150115

Priority
• IT TO20140028 A 20140117
• EP 15705705 A 20150115
• IB 2015050303 W 20150115

Abstract (en)
A dishwashing machine has a load-bearing structure that comprises a base supporting a washtub (3), there being articulated to the load-bearing structure a front door (4) of the washtub (3), the machine (1) moreover having a system for extraction of damp air from the tub (3), which comprises a fan (7) and a discharge duct (8) having a hollow body (9) with a width dimension and a height dimension. The fan (7) is a radial fan having a fan housing (7a), housed in which is a centrifugal impeller (7b), and the discharge duct (8) has an inlet portion (10) and an outlet portion (11). The intake mouth (7c) of the fan (7) is in fluid communication with an outlet opening (15) of the tub (3), the inlet portion (10) of the discharge duct (8) is in fluid communication with the delivery (7d) of the fan (7) and the outlet portion (11) of the discharge duct (8) is at the front of the machine (1). The discharge duct (8) has a portion (12) intermediate with respect to the inlet and outlet portions (10, 11) having a height (H) that decreases towards the outlet portion (11) and a width (W) that increases towards the outlet portion (11). At least the outlet portion (11) and the intermediate portion (12) of the discharge duct (8) extend over an upper wall (3a) of the tub (3), with the outlet portion (11) above an upper edge of the door (4). The outlet opening (15) is formed in one of the upper wall (3a) and a stationary side wall (3 c) of the tub (3), with the fan housing (7a) that is mounted on the aforesaid wall with the respective intake mouth (7c) that is at the outlet opening (15) and is substantially coaxial thereto. The damp air is drawn in from the outlet opening (15) substantially in the direction of the axis (A) of the impeller (7b) and forced in a radial direction into the discharge duct (8), and then expelled from the outlet portion (11) at the front of the machine (1) above the upper edge of the door (4).

IPC 8 full level
A47L 15/48 (2006.01)

CPC (source: EP)
A47L 15/486 (2013.01); **A47L 15/488** (2013.01)

Citation (applicant)
• FR 2491322 A1 19820409 - BOSCH SIEMENS HAUSGERAETE [DE]
• EP 0752232 A1 19970108 - MERLONI ELETTRODOMESTICI SPA [IT]
• EP 0556773 A1 19930825 - MERLONI ELETTRODOMESTICI SPA [IT]
• EP 0721762 A1 19960717 - MERLONI ELETTRODOMESTICI SPA [IT]
• US 2008202557 A1 20080828 - GONSKA HEINRICH [DE], et al

Citation (search report)
• [A] US 2008202557 A1 20080828 - GONSKA HEINRICH [DE], et al
• [A] WO 2009008828 A1 20090115 - ASKO CYLINDA AB [SE], et al
• [A] EP 1721559 A1 20061115 - ELECTROLUX HOME PROD CORP [BE]
• [A] EP 1961361 A1 20080827 - ELECTROLUX HOME PROD CORP [BE], et al

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
WO 2015107474 A1 20150723; EP 3094230 A1 20161123; EP 3094230 B1 20220406; EP 3998009 A1 20220518; EP 3998009 B1 20230329

DOCDB simple family (application)
IB 2015050303 W 20150115; EP 15705705 A 20150115; EP 21210074 A 20150115