

Title (en)

PROCESS FOR PRODUCING A POLYMER COMPOSITION

Title (de)

VERFAHREN ZUR HERSTELLUNG EINER POLYMERZUSAMMENSETZUNG

Title (fr)

PROCÉDÉ POUR LA PRODUCTION D'UNE COMPOSITION DE POLYMÈRES

Publication

**EP 3999565 A1 20220525 (EN)**

Application

**EP 20737483 A 20200715**

Priority

- EP 19186848 A 20190717
- EP 2020069926 W 20200715

Abstract (en)

[origin: WO2021009189A1] The present invention concerns a process for producing a polymer composition characterized in that a first ethylene polymer component (A) is obtained in a first polymerization zone by polymerization conducted in slurry in the presence of ethylene, optionally at least one comonomer selected from alpha-olefins having from 4 to 10 carbon atoms and optionally hydrogen and a second ethylene polymer component (B) is obtained in a second polymerization zone by polymerization conducted in slurry in the presence of ethylene, first ethylene polymer component (A), optionally at least one comonomer selected from alpha-olefins having from 4 to 10 carbon atoms and optionally hydrogen and a third ethylene polymer component (C) is obtained in a third polymerization zone by polymerization conducted in gas phase in the presence of ethylene, optionally hydrogen and at least one comonomer selected from alpha-olefins having from 4 to 10 carbon atoms, to produce a multimodal polymer of ethylene (a) with at least one comonomer selected from alpha-olefins having from 4 to 10 carbon atoms, - which has a) a density between 900 and 960 kg/m<sup>3</sup> b) MFR2 of 0.1 to 25 g/10 min (according to ISO 1133 at 190 °C under 2.16 kg load), c) MWD of 2 to 6, - which comprises at least - between 10 to < 25 wt% of an ethylene polymer component (A), - between 10 to < 25 wt% of an ethylene polymer component (B) and - between > 50 and 80 wt% of an ethylene polymer component (C) and wherein the densities of ethylene polymer components (A) and (B) are each between 925 and 970 kg/m<sup>3</sup> and the density of ethylene polymer component (C) has a density between 880 and 950 kg/m<sup>3</sup>, wherein further the ethylene polymer components (A), (B) and (C) have different MFR2 values.

IPC 8 full level

**C08F 210/16** (2006.01); **C08F 2/00** (2006.01); **C08F 4/6592** (2006.01); **C08F 210/08** (2006.01); **C08F 210/14** (2006.01); **C08J 5/18** (2006.01)

CPC (source: CN EP)

**C08F 210/16** (2013.01 - CN EP); **C08J 5/18** (2013.01 - CN EP); **C08F 4/65912** (2013.01 - EP); **C08F 4/65916** (2013.01 - EP);  
**C08J 2323/08** (2013.01 - CN EP); **C08L 2205/03** (2013.01 - EP); **C08L 2314/06** (2013.01 - EP)

Citation (search report)

See references of WO 2021009189A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

**WO 2021009189 A1 20210121**; CN 114402003 A 20220426; CN 114402003 B 20230418; EP 3999565 A1 20220525

DOCDB simple family (application)

**EP 2020069926 W 20200715**; CN 202080061708 A 20200715; EP 20737483 A 20200715