

Title (en)
UNWINDING SECTION AND A METHOD FOR REMOVING SLAB FIBER WEB FROM A REELING SHAFT

Title (de)
ABWICKLUNGSABSCHNITT UND VERFAHREN ZUM ENTFERNEN VON PLATTENFASERBAHN VON EINER WICKELWELLE

Title (fr)
SECTION DE DÉROULEMENT ET PROCÉDÉ D'ÉLIMINATION DE TOILE DE DALLE EN FIBRES À PARTIR D'UN ARBRE D'ENROULEMENT

Publication
EP 4005956 B1 20231129 (EN)

Application
EP 21201563 A 20211008

Priority
FI 20206106 A 20201105

Abstract (en)
[origin: EP4005956A1] The invention relates to an unwinding section for unwinding a fiber web (W) from a parent roll (12) wound around a reeling shaft (10), which unwinding section (15) comprises two unwinding positions (I, II) consisting of a first unwinding position (I) and a second unwinding position (II), in which unwinding section (15) the unwinding of the parent roll (12) is configured to be begun at the first unwinding position (I) and in which unwinding section (15) towards end of the unwinding the parent roll (12) is configured to be transferred to the second unwinding position (II), which unwinding section (15) comprises a broke opening (26). The unwinding section (15) comprises a slabbing device (35) configured to operate in area of the first and second unwinding positions (I, II). The slabbing device (35) is configured to pick up a slab fiber web (RW) from a reject roll (13) formed of a fiber web remaining on the reeling shaft (10) after the unwinding of the parent roll (12) is finished in the second unwinding position (II) and the slabbing device (35) is configured to empty the slab fiber web (RW) through the broke opening (26). The invention also relates to a method for removing slab fiber web from a reeling shaft for removing slab fiber web from a reeling shaft (10) in an unwinding section (15) comprising two unwinding positions (I, II) consisting of a first unwinding position (I) and a second unwinding position (II) and comprising a broke opening (26), in which method in the unwinding section (15) the unwinding of the parent roll (12) is begun at the first unwinding position (I) and towards end of the unwinding the parent roll (12) is transferred to the second unwinding position (II). In the method the slab fiber web (RW) is removed by a slabbing device (35) operating in area of the first and second unwinding positions (I, II), the slab fiber web (RW) from a reject roll (13) formed of a fiber web remaining on the reeling shaft (10) after the unwinding of the parent roll (12) is finished in the second unwinding position (II) is picked up by the slabbing device (35) and the slab fiber web (RW) is emptied from the slabbing device (35) through the broke opening (26).

IPC 8 full level
B65H 16/06 (2006.01); **B65H 19/12** (2006.01)

CPC (source: CN EP FI)
B65H 16/00 (2013.01 - FI); **B65H 16/10** (2013.01 - CN); **B65H 19/126** (2013.01 - EP); **B65H 73/00** (2013.01 - FI); **B65H 2301/41342** (2013.01 - EP); **B65H 2301/41361** (2013.01 - EP); **B65H 2301/4148** (2013.01 - EP); **B65H 2301/41734** (2013.01 - EP); **B65H 2301/543** (2013.01 - EP); **B65H 2801/84** (2013.01 - EP)

Citation (examination)
DE 102005000173 A1 20070606 - VOITH PATENT GMBH [DE]

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 4005956 A1 20220601; **EP 4005956 B1 20231129**; CN 114436002 A 20220506; CN 114436002 B 20240123; FI 129371 B 20211231; FI 20206106 A1 20211231

DOCDB simple family (application)
EP 21201563 A 20211008; CN 202111293690 A 20211103; FI 20206106 A 20201105