

Title (en)

SEWING MACHINE NEEDLE WITH RECESS

Title (de)

NÄHMASCHINENNADDEL MIT AUSNEHMUNG

Title (fr)

AIGUILLE POUR MACHINE À COUDRE À ÉVIDEMENT

Publication

EP 4015692 C0 20230621 (DE)

Application

EP 20214663 A 20201216

Priority

EP 20214663 A 20201216

Abstract (en)

[origin: WO2022128295A1] The invention relates to a sewing machine needle (1) which reduces the friction between the shaft of the sewing machine needle (1) and the sewing item and which thereby can be produced economically in large numbers. The sewing machine needle (1) comprises a needle eye (3) and at least one recess (5), wherein the distance of an upper edge (6) of the recess (5) to the width position of the axis (12) of the needle eye (3) is different from the distance of a lower edge (7) of the recess (5) to the width position of the axis (12) of the needle eye (3).

IPC 8 full level

D05B 85/00 (2006.01); **B21G 1/04** (2006.01)

CPC (source: EP KR US)

B21G 1/04 (2013.01 - US); **D05B 85/00** (2013.01 - EP KR US); **B21G 1/04** (2013.01 - EP)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated validation state (EPC)

MA TN

Participating member state (EPC – UP)

AT BE BG DE DK EE FI FR IT LT LU LV MT NL PT SE SI

DOCDB simple family (publication)

EP 4015692 A1 20220622; **EP 4015692 B1 20230621**; **EP 4015692 C0 20230621**; CN 116669876 A 20230829; ES 2955796 T3 20231207; JP 2023553480 A 20231221; KR 20230118886 A 20230814; MX 2023007243 A 20230629; PL 4015692 T3 20231120; TW 202233931 A 20220901; US 2024026587 A1 20240125; WO 2022128295 A1 20220623

DOCDB simple family (application)

EP 20214663 A 20201216; CN 202180085444 A 20211117; EP 2021081981 W 20211117; ES 20214663 T 20201216; JP 2023535944 A 20211117; KR 20237022252 A 20211117; MX 2023007243 A 20211117; PL 20214663 T 20201216; TW 110144325 A 20211129; US 202118265853 A 20211117