

Title (en)
DIVERTER ASSEMBLY FOR SECURITY LOCKS AND RELATED LOCK

Title (de)
UMLENKUNGSANORDNUNG FÜR SICHERHEITSSCHLÖSSER UND ENTSPRECHENDES SCHLOSS

Title (fr)
ENSEMBLE DÉVIATEUR POUR SERRURES DE SÉCURITÉ ET SERRURE ASSOCIÉE

Publication
EP 4023841 A1 20220706 (EN)

Application
EP 20217540 A 20201229

Priority
EP 20217540 A 20201229

Abstract (en)
Diverter assembly (100, 200, 200', 300) for locks (400, 500) and lock (400, 500) comprising said diverter assembly (100, 200, 200', 300), said diverter assembly comprising: a casing (11, 21, 31), at least one bolt (13, 14, 23, 24, 33, 34, 33', 34') comprising: a hollow cylinder (13, 23, 33, 33') configured to move from a first position wherein it is inside the casing (11, 21, 31) to a second position wherein it is at least partially outside the casing (11, 21, 31), and a pin (14, 24, 34, 34'); a slider (15, 25, 35) comprising a plate provided with at least one slot (16, 26, 36, 36') for each cylinder (13, 23, 33, 33'), in said slot (16, 26, 36, 36') being engaged the pin (14, 24, 34, 34') of the bolt (13, 23, 33, 33', 14, 24, 34, 34'), said slider (15, 25, 35) being configured to translate from a first position wherein the pin (14, 24, 34, 34') is positioned at a first end (16', 26', 136, 136') of the slot (16, 26, 36, 36') to a second position wherein the pin (14, 24, 34, 34') is positioned at a second end (16'', 26'', 236, 236'') of the slot (16, 26, 36, 36'); the lateral surface of the cylinder (13, 23, 33, 33') being provided with two longitudinal slits (18, 18') diametrically opposed one to the other and configured in such a way that the plate of the slider (15, 25, 35) can slide in their interior; and the pin (14, 24, 34, 34') being mounted inside the cylinder (13, 23, 33, 33') so as to be parallel to the base surfaces of the cylinder (13, 23, 33, 33'), the slits (18, 18') and the pin (14, 24, 34, 34') being positioned in such a way that, when the slider (15, 25, 35) is in its first position, the cylinder (13, 23, 33, 33') is in its first position and, when the slider (15, 25, 35) is in its second position, the cylinder (13, 23, 33, 33') is in its second position.

IPC 8 full level
E05B 15/10 (2006.01); **E05B 55/00** (2006.01); **E05B 55/12** (2006.01); **E05B 59/00** (2006.01); **E05B 63/02** (2006.01); **E05B 65/10** (2006.01); **E05C 1/00** (2006.01); **E05C 1/06** (2006.01); **E05C 9/04** (2006.01); **E05C 9/18** (2006.01); **E05B 63/00** (2006.01)

CPC (source: EP)
E05B 15/10 (2013.01); **E05B 59/00** (2013.01); **E05C 1/002** (2013.01); **E05C 1/06** (2013.01); **E05C 9/041** (2013.01); **E05C 9/042** (2013.01); **E05C 9/1841** (2013.01); **E05B 63/0056** (2013.01)

Citation (search report)
• [A] DE 2810058 A1 19780921 - CAVERS S A R L ETS
• [A] EP 0707123 A2 19960417 - FLIETHER KARL GMBH & CO [DE]
• [A] EP 1473424 A1 20041103 - PRATI & NEGRI SNC [IT]
• [A] EP 3741950 A1 20201125 - VEKA AG [DE], et al

Cited by
EP4345234A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
EP 4023841 A1 20220706; **EP 4023841 B1 20231122**; **EP 4023841 C0 20231122**; ES 2972370 T3 20240612

DOCDB simple family (application)
EP 20217540 A 20201229; ES 20217540 T 20201229