

Title (en)  
VALVE FOR METERING A FLUID

Title (de)  
VENTIL ZUM ZUMESSEN EINES FLUIDS

Title (fr)  
SOUPAPE DE DISTRIBUTION D'UN FLUIDE

Publication  
**EP 4033087 A1 20220727 (DE)**

Application  
**EP 22157406 A 20180503**

Priority  
• EP 18722483 A 20180503  
• DE 102017207845 A 20170510  
• EP 2018061296 W 20180503

Abstract (en)  
[origin: WO2018206382A1] A valve (1) for metering a fluid, which valve serves, in particular, as a fuel injection valve for internal combustion engines, comprises an electromagnetic actuator (10) which has an armature (6) which is arranged in an armature space (16), and a valve needle (5) which can be operated by the actuator (10) by means of the armature (6), wherein the armature (6) is guided on the valve needle (5), wherein a first stop element (7), which interacts with a first end side (22) of the armature (6) during operation, and a second stop element (8), which interacts with a second end side (23) of the armature (6) during operation, are arranged on the valve needle (5) and limit a movement of the armature (6) relative to the valve needle (5), and wherein the armature (6) has a spring receptacle (25) which is open in the direction of the first end side (22) of the armature (6) and into which a spring (27), which is supported on the stop element (7), is inserted. Here, the valve (1) is embodied such that the armature (6) has at least one fluid channel (15) which, during operation, allows fluid to flow between a first region (17) of the armature space (16), which first region adjoins the first end side (22) of the armature (6), and a second region (18) of the armature chamber (16), which second region adjoins the second end side (23) of the armature (6), that the fluid channel (15) at least partially incorporates the spring receptacle (25), and that the fluid channel (15) runs at least in sections radially outward along a direction (19) which is oriented from the first end side (22) to the second end side (23) and is coaxial with respect to a longitudinal axis (4).

Abstract (de)  
Ein Ventil (1) zum Zumessen eines Fluids, das insbesondere als Brennstoffeinspritzventil für Brennkraftmaschinen dient, umfasst einem elektromagnetischen Aktuator (10), der einen in einem Ankerraum (16) angeordneten Anker (6) aufweist, und einer von dem Aktuator (10) mittels des Ankers (6) betätigbaren Ventilnadel (5), wobei der Anker (6) an der Ventilnadel (5) geführt ist, wobei an der Ventilnadel (5) ein im Betrieb mit einer ersten Stirnseite (22) des Ankers (6) zusammenwirkendes erstes Anschlagelement (7) und ein im Betrieb mit einer zweiten Stirnseite (23) des Ankers (6) zusammenwirkendes zweites Anschlagelement (8) angeordnet sind, die eine Bewegung des Ankers (6) relativ zu der Ventilnadel (5) begrenzen, und wobei der Anker (6) eine zu der ersten Stirnseite (22) des Ankers (6) hin offene Federaufnahme (25) aufweist, in die eine an dem Anschlagelement (7) abgestützte Feder (27) eingesetzt ist. Das Ventil (1) ist hierbei so ausgestaltet, dass der Anker (6) zumindest einen Fluidkanal (15) aufweist, der im Betrieb eine Durchleitung von Fluid zwischen einem an die erste Stirnseite (22) des Ankers (6) angrenzenden ersten Bereich (17) des Ankerraums (16) und einem an die zweite Stirnseite (23) des Ankers (6) angrenzenden zweiten Bereich (18) des Ankerraums (16) ermöglicht, dass der Fluidkanal (15) zumindest teilweise die Federaufnahme (25) einbezieht und dass der Fluidkanal (15) entlang einer von der ersten Stirnseite (22) zu der zweiten Stirnseite (23) orientierten und bezüglich einer Längsachse (4) koaxialen Richtung (19) zumindest abschnittsweise radial nach außen verläuft.

IPC 8 full level  
**F02M 51/06** (2006.01)

CPC (source: CN EP KR US)  
**B05B 1/3053** (2013.01 - US); **F02M 51/0671** (2013.01 - EP KR); **F02M 51/0685** (2013.01 - EP KR US); **F02M 55/008** (2013.01 - KR); **F02M 61/10** (2013.01 - CN US); **F02M 61/1893** (2013.01 - CN); **F02M 55/008** (2013.01 - EP); **F02M 2200/304** (2013.01 - EP KR)

Citation (applicant)  
DE 102013222613 A1 20150507 - BOSCH GMBH ROBERT [DE]

Citation (search report)  
• [A] JP 2015218664 A 20151207 - DENSO CORP  
• [A] WO 0125614 A1 20010412 - BOSCH GMBH ROBERT [DE], et al  
• [A] EP 3156638 A1 20170419 - CONTINENTAL AUTOMOTIVE GMBH [DE]  
• [A] WO 0218776 A1 20020307 - BOSCH GMBH ROBERT [DE], et al  
• [A] WO 0129402 A1 20010426 - BOSCH GMBH ROBERT [DE], et al  
• [A] EP 3009663 A1 20160420 - CONTINENTAL AUTOMOTIVE GMBH [DE]  
• [A] EP 2918816 A1 20150916 - CONTINENTAL AUTOMOTIVE GMBH [DE]

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)  
**DE 102017207845 A1 20181115**; CN 110612390 A 20191224; CN 110612390 B 20220531; CN 114876689 A 20220809; CN 114876689 B 20230901; EP 3622170 A1 20200318; EP 3779172 A1 20210217; EP 3779172 B1 20220706; EP 4033087 A1 20220727; EP 4033087 B1 20230830; JP 2020519805 A 20200702; JP 2021179214 A 20211118; JP 7270684 B2 20230510; KR 102673915 B1 20240612; KR 102678806 B1 20240628; KR 20200003824 A 20200110; KR 20230043253 A 20230330; US 11852106 B2 20231226; US 2020386199 A1 20201210; WO 2018206382 A1 20181115

DOCDB simple family (application)  
**DE 102017207845 A 20170510**; CN 201880030629 A 20180503; CN 202210637776 A 20180503; EP 18722483 A 20180503; EP 2018061296 W 20180503; EP 20191515 A 20180503; EP 22157406 A 20180503; JP 2019561825 A 20180503; JP 2021125734 A 20210730; KR 20197033138 A 20180503; KR 20237010013 A 20180503; US 201816607140 A 20180503