Title (en)

CABINET DRAWER

Title (de)

SCHRANKAUSZUG

Title (fr)

TIROIR D'ARMOIRE

Publication

EP 4037527 A1 20220810 (DE)

Application

EP 20788995 A 20200922

Priority

- DE 102019126353 A 20190930
- EP 2020076417 W 20200922

Abstract (en)

[origin: WO2021063749A1] The invention relates to a cabinet drawer (1), in particular for tall cabinets, comprising a frame (4) which is to be arranged in the interior of the cabinet body (2) and has a cabinet door (3) or a similar cabinet covering on the front face on a vertical longitudinal support (6). The frame (4), which has a respective support base (7), can be moved out of a first operating position, which lies within the cabinet body (2), into a pull-out position, which lies in front of the cabinet body (2), as a second operating position in a translational manner, and the frame (4), which has an upper (8) and a lower (9) pull-out rail, can be converted into the second operating position using a rear vertical longitudinal support (5) such that the frame (4) can be pivoted about a vertical pivot axis in the second operating position. The cabinet drawer (1) is paired with a blocking device (13) which prevents the frame (4) from carrying out a pivoting movement before reaching the second operating position and releases the frame (4) to carry out a pivoting movement in the second operating position. The aim of the invention is to improve such a cabinet drawer (1). This is achieved in that the blocking device (13) has a slotted gate part (14) which can be pivoted about a vertical axis and comprises a guide path (15), the slotted gate part (14) together with the frame (4) can be moved into the second operating position, a guide part (14) is arranged within the frame (4) is a part of the pivoting movement of the frame, and the slotted gate part (14) is arranged within the frame (4) is prevented from carrying out a pivoting movement of the frame (4) into the second operating position as to be prevented from the guide path (15) of the slotted gate part (14) during a part of the pivoting movement of the frame, and the slotted gate part (14) is arranged within the blocking device (13) in the course of the translational movement of the frame (4) into the second operating position so as to be prevented from carrying

IPC 8 full level

A47B 88/42 (2017.01); A47B 88/48 (2017.01)

CPC (source: EP US)

A47B 61/02 (2013.01 - US); A47B 88/42 (2017.01 - EP US); A47B 88/48 (2017.01 - EP US); A47B 2210/0081 (2013.01 - US)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC) BA ME

DOCDB simple family (publication)

DE 102019126353 B3 20210121; AU 2020360042 A1 20220519; CN 114828696 A 20220729; EP 4037527 A1 20220810; EP 4037527 B1 20231220; PL 4037527 T3 20240506; US 11910924 B2 20240227; US 2022378202 A1 20221201; WO 2021063749 A1 20210408

DOCDB simple family (application)

DE 102019126353 A 20190930; AU 2020360042 A 20200922; CN 202080079827 A 20200922; EP 2020076417 W 20200922; EP 20788995 A 20200922; PL 20788995 T 20200922; US 202017765205 A 20200922