

Title (en)

METHOD FOR AUTHENTICATING A SECURE ELEMENT AT THE LEVEL OF AN AUTHENTICATION SERVER, CORRESPONDING SECURE ELEMENT AND AUTHENTICATION SERVER

Title (de)

VERFAHREN ZUR AUTHENTIFIZIERUNG EINES SICHEREN ELEMENTS AUF DER EBENE EINES AUTHENTIFIZIERUNGSSERVERS, ZUGEHÖRIGES SICHERES ELEMENT UND AUTHENTIFIZIERUNGSSERVER

Title (fr)

PROCÉDÉ D'AUTHENTIFICATION D'UN ÉLÉMENT SÉCURISÉ AU NIVEAU D'UN SERVEUR D'AUTHENTIFICATION, ÉLÉMENT SÉCURISÉ CORRESPONDANT ET SERVEUR D'AUTHENTIFICATION

Publication

**EP 4074087 A1 20221019 (EN)**

Application

**EP 20803563 A 20201110**

Priority

- EP 19306651 A 20191213
- EP 2020081566 W 20201110

Abstract (en)

[origin: EP3836589A1] The invention concerns a method for authenticating a secure element 10 at the level of an authentication server 12, the secure element 10 being able to cooperate with a telecommunication terminal, the method comprising:- Generating at the secure element 10 a first message comprising a partial IMSI of the secure element 10 or a partial IMSI of an IMSI based user identity that is in the form of a NAI of the secure element, called MSIN\_part1, the first message also comprising the MCC and MNC codes of the IMSI or of the IMSI based user identity that is in the form of a NAI of the secure element 10, the MSIN\_part1 comprising some of the most significant digits of the MSIN;- Generating at the secure element 10 a second message containing a second part, called MSIN\_part2, of the MSIN of the secure element 10 and the current sequence number, the second message being encrypted by the key Ki of the secure element 10 in order to provide a token X, the MSIN\_part2 comprising some of the less significant digits of the MSIN;- Transmitting the first message and the token X to the authentication server 12;- At the authentication server 12, creating a list of the candidate secure elements for which the MSIN\_part1 corresponds and, for each of the candidate secure elements of the list, decrypting the token X with the key Ki of each of the candidate secure elements of the list, in order to generate a decrypted IMSI comprising the MCC, MNC and MSIN\_part1 of the first message and decrypted MSIN\_part2 of the token X or a decrypted IMSI based user identity that is in the form of a NAI comprising the MCC, MNC and MSIN\_part1 of the first message and the decrypted MSIN\_part2 of the token X;- Checking at the authentication server 12, for each candidate secure element of the list, which candidate IMSI or candidate IMSI based user identity that is in the form of a NAI :a corresponds to the decrypted IMSI of the decrypted token X; andb has an associated sequence number in a valid range of the decrypted sequence number;- At the authentication server 12, generating an authentication vector by using the key Ki of the candidate secure element associated to the IMSI or IMSI based user identity that is in the form of a NAI that matches the decrypted MSIN\_part2 of the decrypted token X and the candidate secure element has sequence number in a valid range of the decrypted sequence number in order to launch a challenge response process between the secure element 10 and the authentication server 12.

IPC 8 full level

**H04W 12/02** (2009.01); **H04W 12/03** (2021.01); **H04W 12/06** (2021.01); **H04W 12/72** (2021.01)

CPC (source: EP)

**H04W 12/02** (2013.01); **H04W 12/03** (2021.01); **H04W 12/06** (2013.01); **H04W 12/72** (2021.01)

Citation (search report)

See references of WO 2021115699A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

**EP 3836589 A1 20210616**; EP 4074087 A1 20221019; WO 2021115699 A1 20210617

DOCDB simple family (application)

**EP 19306651 A 20191213**; EP 2020081566 W 20201110; EP 20803563 A 20201110