

Title (en)

SEALED REFRIGERANT COMPRESSOR AND FREEZING/REFRIGERATION DEVICE USING SAME

Title (de)

DICHTER KÄLTEMITTELVERDICHTER UND DIESE VERWENDENDE GEFRIER-/KÜHLVORRICHTUNG

Title (fr)

COMPRESSEUR FRIGORIFIQUE HERMÉTIQUE ET DISPOSITIF DE CONGÉLATION/FRIGORIFIQUE LE METTANT EN OEUVRE

Publication

**EP 4089282 A1 20221116 (EN)**

Application

**EP 20896484 A 20201202**

Priority

- JP 2019218529 A 20191203
- JP 2020044763 W 20201202

Abstract (en)

In a hermetic refrigerant compressor, a thrust bearing (e.g., thrust ball bearing (210)) is provided on a thrust surface (136) of a main bearing (134). One end of a sliding surface of the main bearing (134), the one end being closer to a compression chamber (133) than an opposite end of the sliding surface, is a first end, and the opposite end of the sliding surface is a second end. A distance between a center axis of the compression chamber (133) and the second end of the sliding surface (sliding surface lower end (139)) of the main bearing (134) is a distance L, and a distance between the center axis of the compression chamber (133) and the first end of the sliding surface (sliding surface upper end (138)) of the main bearing (134) is a distance La. When the distance L is in a range of 38 mm to 51 mm, the distance La is less than or equal to 16 mm.

IPC 8 full level

**F04B 39/00** (2006.01); **F04B 39/02** (2006.01); **F25B 1/02** (2006.01)

CPC (source: EP US)

**F04B 35/04** (2013.01 - EP); **F04B 39/00** (2013.01 - EP); **F04B 39/0094** (2013.01 - EP); **F04B 39/023** (2013.01 - EP US);  
**F04B 39/0246** (2013.01 - EP); **F04B 39/122** (2013.01 - EP); **F25B 1/02** (2013.01 - EP); **F25B 31/023** (2013.01 - EP); **F25B 31/026** (2013.01 - US)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

Designated validation state (EPC)

KH MA MD TN

DOCDB simple family (publication)

**EP 4089282 A1 20221116; EP 4089282 A4 20240320**; CN 114930023 A 20220819; JP 2023033383 A 20230310;  
JP WO2021112105 A1 20210610; US 2023003426 A1 20230105; WO 2021112105 A1 20210610

DOCDB simple family (application)

**EP 20896484 A 20201202**; CN 202080092642 A 20201202; JP 2020044763 W 20201202; JP 2021562673 A 20201202;  
JP 2023001085 A 20230106; US 202017782363 A 20201202