

Title (en)

FEED DEVICE FOR A CARTRIDGE MAGAZINE FOR A HANDGUN, FEED DEVICE UNIT FOR A CARTRIDGE MAGAZINE FOR A HANDGUN, CARTRIDGE MAGAZINE FOR A HANDGUN, AND METHOD FOR OPERATING A HANDGUN

Title (de)

ZUBRINGER FÜR EIN PATRONENMAGAZIN FÜR EINE HANDFEUERWAFFE, ZUBRINGEREINHEIT FÜR EIN PATRONENMAGAZIN FÜR EINE HANDFEUERWAFFE, PATRONENMAGAZIN FÜR EINE HANDFEUERWAFFE UND VERFAHREN ZUM BETREIBEN EINER HANDFEUERWAFFE

Title (fr)

PLANCHETTE ÉLÉVATRICE POUR CHARGEUR DE CARTOUCHES D'UNE ARME À FEU PORTATIVE, ENSEMBLE PLANCHETTE ÉLÉVATRICE POUR UN CHARGEUR DE CARTOUCHES D'UNE ARME À FEU PORTATIVE, CHARGEUR DE CARTOUCHES POUR UNE ARME À FEU PORTATIVE ET PROCÉDÉ POUR FAIRE FONCTIONNER UNE ARME À FEU PORTATIVE

Publication

**EP 4094033 A1 20221130 (DE)**

Application

**EP 21705103 A 20210118**

Priority

- DE 102020000298 A 20200120
- EP 2021000004 W 20210118

Abstract (en)

[origin: WO2021148233A1] The invention relates to a feed device (1) for a cartridge magazine (2) for a handgun. The feed device extends along a first spatial direction (X), a second spatial direction (Y), and a third spatial direction (Z) and in the process forms an upper region (I), a lower region (II), a rear region (III), and a front region (IV), wherein the feed device (1) has a first cartridge contact surface (3) and a second cartridge contact surface (4) on the upper region (I), said contact surfaces being mutually spaced in the third spatial direction (Z), and each contact surface is designed such that a cartridge (P) for a handgun can be moved on said contact surface along the direction of the front region (IV). The feed device (1) additionally has a front guide part (5) which forms at least one front support surface (6) and a rear guide part (7) which forms at least one rear support surface (8). At least some of the disadvantages of the prior art mentioned in the introductory section of the present invention are to be overcome. This is achieved in that the rear support surface (8) is made of at least one first support surface (8a) and a second support surface (8b), the first support surface (8a) is formed on a fixed part (7a) of the rear guide part (7), and the second support surface (8b) is formed on a movable part (7b) of the rear guide part. The invention additionally relates to a feed device unit, to a cartridge magazine, and to a method for operating a handgun.

IPC 8 full level

**F41A 9/70** (2006.01); **F41A 17/36** (2006.01)

CPC (source: EP US)

**F41A 9/70** (2013.01 - EP US); **F41A 17/36** (2013.01 - EP US)

Citation (search report)

See references of WO 2021148233A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

Designated validation state (EPC)

KH MA MD TN

DOCDB simple family (publication)

**DE 102020000298 A1 20210722**; **DE 102020000298 B4 20220811**; EP 4094033 A1 20221130; US 2022357120 A1 20221110; WO 2021148233 A1 20210729

DOCDB simple family (application)

**DE 102020000298 A 20200120**; EP 2021000004 W 20210118; EP 21705103 A 20210118; US 202217869545 A 20220720