

Title (en)
SEAMING DEVICE

Title (de)
FALZVORRICHTUNG

Title (fr)
DISPOSITIF DE SERTISSAGE

Publication
EP 4119255 A1 20230118 (EN)

Application
EP 20924414 A 20201130

Priority

- JP 2020044475 W 20201130
- JP 2020044198 A 20200313
- JP 2020044199 A 20200313
- JP 2020044200 A 20200313
- JP 2020044201 A 20200313
- JP 2020044202 A 20200313

Abstract (en)
The present invention has an object of providing a seaming device that does not need the supply of a lubricant at a high pressure from an outside, obtains a sufficient flow rate while suppressing the leakage of the lubricant, and obtains sufficient lubricating performance and heat exhausting performance even when the seaming device is used at a low speed or at a high load. Seaming rolls (451) and (452) have, therein, a lubricant pump mechanism that transfers a lubricating oil between a lubricant path (454) of a seaming roll pin (453) and a bearing (458).

IPC 8 full level
B21D 51/30 (2006.01)

CPC (source: EP US)
B21D 43/06 (2013.01 - EP); **B21D 51/2653** (2013.01 - EP); **B21D 51/2692** (2013.01 - EP US); **B21D 51/32** (2013.01 - US); **B65B 7/2807** (2013.01 - US); **B21D 43/16** (2013.01 - EP); **B21D 51/32** (2013.01 - EP); **B65B 7/2807** (2013.01 - EP); **B65B 7/285** (2013.01 - EP)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

Designated validation state (EPC)
KH MA MD TN

DOCDB simple family (publication)
EP 4119255 A1 20230118; **EP 4119255 A4 20240424**; CN 115279512 A 20221101; TW 202144275 A 20211201; TW I834942 B 20240311; WO 2021181764 A1 20210916

DOCDB simple family (application)
EP 20924414 A 20201130; CN 202080098286 A 20201130; JP 2020044475 W 20201130; TW 110101194 A 20210113