

Title (en)
AXIAL FAN, BLOWING DEVICE, AND REFRIGERATION CYCLE DEVICE

Title (de)
AXIALLÜFTER, GEBLÄSEVORRICHTUNG UND KÄLTEKREISLAUFVORRICHTUNG

Title (fr)
VENTILATEUR AXIAL, DISPOSITIF DE SOUFFLAGE, ET DISPOSITIF À CYCLE FRIGORIFIQUE

Publication
EP 4130487 A4 20230503 (EN)

Application
EP 20927809 A 20200324

Priority
JP 2020013027 W 20200324

Abstract (en)
[origin: EP4130487A1] An axial fan includes a hub, and a blade. The hub has a rotational axis, and is configured to be driven to rotate. The blade is connected to the hub, and has a front edge and a rear edge. In a shape of the blade as viewed in a cross section perpendicular to the rotational axis and in a part nearer to a pressure surface of the blade, the blade has a region in which a distance ratio $L2/L1$ increases in a direction from the front edge to the rear edge, where: a front end of a mountain-like portion formed to be convex in a rotation direction of the blade is defined as a vertex portion; a vertex portion positioned nearest to an inner circumference is defined as a vertex portion P_i ; a vertex portion positioned nearest to an outer circumference is defined as a vertex portion P_o ; a position of a radius centering around the rotational axis and including the vertex portion P_i is defined as a radius position R_i ; a position of a radius centering around the rotational axis and including the vertex portion P_o is defined as a radius position R_o ; a position of a radius in the middle between the radius position R_i and the radius position R_o is defined as a radius position R_c ; a position of a radius in the middle between the radius position R_i and the radius position R_c is defined as a radius position R_1 ; a position of a radius in the middle between the radius position R_o and the radius position R_c is defined as a radius position R_2 ; a virtual straight line connecting the vertex portion P_i and the vertex portion P_o is defined as a reference line SL ; at the radius position R_1 , a distance between the reference line SL and the pressure surface is defined as a distance L_1 ; at the radius position R_2 , a distance between the reference line SL and the pressure surface is defined as a distance L_2 ; and a ratio between the distance L_1 and the distance L_2 is defined as the distance ratio $L2/L1$.

IPC 8 full level
F04D 29/38 (2006.01)

CPC (source: EP)
F04D 29/384 (2013.01); **F05D 2240/301** (2013.01); **F05D 2240/305** (2013.01); **F05D 2250/182** (2013.01); **F05D 2250/611** (2013.01)

Citation (search report)

- [XA] EP 3085966 A1 20161026 - MITSUBISHI ELECTRIC CORP [JP]
- [A] WO 2018158859 A1 20180907 - MITSUBISHI ELECTRIC CORP [JP]
- [A] US 2019107118 A1 20190411 - ARAI TOSHIKATSU [JP], et al
- [A] WO 2016071948 A1 20160512 - MITSUBISHI ELECTRIC CORP [JP]
- See references of WO 2021192036A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

Designated validation state (EPC)
KH MA MD TN

DOCDB simple family (publication)
EP 4130487 A1 20230208; **EP 4130487 A4 20230503**; CN 115280020 A 20221101; CN 115280020 B 20231205; JP 7258225 B2 20230414; JP WO2021192036 A1 20210930; WO 2021192036 A1 20210930

DOCDB simple family (application)
EP 20927809 A 20200324; CN 202080098663 A 20200324; JP 2020013027 W 20200324; JP 2022509831 A 20200324