

Title (en)  
ELEVATOR DEVICE AND JAMB MOUNTING STRUCTURE THEREFOR

Title (de)  
AUFZUGSVORRICHTUNG UND STAURAHMENMONTAGESTRUKTUR DAFÜR

Title (fr)  
DISPOSITIF D'ASCENSEUR ET STRUCTURE DE MONTAGE DE MONTANT ASSOCIÉE

Publication  
**EP 4151580 A1 20230322 (EN)**

Application  
**EP 20934893 A 20200512**

Priority  
JP 2020019013 W 20200512

Abstract (en)  
The purpose of the invention is to increase an adjustment allowance of a connection component for connecting a jamb to a building wall corresponding to a building construction error. A structure for mounting a jamb 20 provided for an opening of a building wall includes vertical frames 20B constituting the jamb 20, which are disposed on both side edges WB2 of the opening WC of the building wall W, fixing members 22A, 22B for fixing the vertical frames 20B to the building wall W, and partition plates 24A, 24B for partitioning each gap between the building wall W and the vertical frame 20B. The fixing members 22A, 22B are separated into the first fixing member 22A disposed at a side of the building wall W, and the second fixing member 22B disposed at a side of the vertical frame 20B. The partition plates 24A, 24B are separated into the first partition plate 24A disposed at a side of the building wall W, and the second partition plate 24B disposed at a side of the vertical frame 20B.

IPC 8 full level  
**B66B 13/30** (2006.01)

CPC (source: EP)  
**B66B 13/306** (2013.01)

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)  
BA ME

Designated validation state (EPC)  
KH MA MD TN

DOCDB simple family (publication)  
**EP 4151580 A1 20230322; EP 4151580 A4 20231227**; CN 115515884 A 20221223; CN 115515884 B 20240614; JP 7406630 B2 20231227; JP WO2021229695 A1 20211118; WO 2021229695 A1 20211118

DOCDB simple family (application)  
**EP 20934893 A 20200512**; CN 202080100706 A 20200512; JP 2020019013 W 20200512; JP 2022522148 A 20200512