

Title (en)
OPERATOR-INDEPENDENT COMPACT SPRING-ACTION SWITCHING MECHANISM AND ELECTROMECHANICAL PROTECTIVE SWITCHING DEVICE

Title (de)
BEDIENERUNABHÄNGIGES KOMPAKTSPRUNGSCHALTWERK UND ELEKTROMECHANISCHES SCHUTZSCHALTGERÄT

Title (fr)
MÉCANISME DE COMMUTATION À RESSORT COMPACT INDÉPENDANT DE L'OPÉRATEUR ET DISPOSITIF DE COMMUTATION DE PROTECTION ÉLECTROMÉCANIQUE

Publication
EP 4176459 A1 20230510 (DE)

Application
EP 21746413 A 20210715

Priority
• DE 102020210028 A 20200807
• EP 2021069763 W 20210715

Abstract (en)
[origin: WO2022028849A1] The invention relates to an operator-independent compact spring-action switching mechanism (10) for an electromechanical protective switching device (1), comprising a switch contact, having a fixed contact (81) and a moving contact (71) that can move relative to same and mounted on a moving contact carrier (70). The compact spring-action switching mechanism (10) has a hand actuation element (41) for manually actuating the compact spring-action switching mechanism (10), which is mechanically coupled to the moving contact carrier (70) in order to manually close or open the switching contact. For this purpose, the compact spring-action switching mechanism (10) has a locking lever (200) which is mechanically coupled to the hand actuation element (41) and can be moved in a first direction (x) pointing in the direction of the switching contact in a first phase of a closing movement of the moving contact (71), in order to block the movement of the moving contact carrier (70), wherein the locking lever (200) abruptly releases the blocking of the moving contact carrier (70) via a movement in a second direction (y) in a second phase of the closing movement, and wherein the compact spring-action switching mechanism (10) has a maximum width of a half horizontal pitch. The operator-independent compact spring-action switching mechanism (10) can also be used for compact protective switching devices (1) due to its space-saving construction and is characterised by significantly improved switch-off behaviour and an extended service life.

IPC 8 full level
H01H 71/02 (2006.01); **H01H 1/50** (2006.01); **H01H 5/04** (2006.01); **H01H 71/24** (2006.01); **H01H 71/52** (2006.01)

CPC (source: EP)
H01H 71/0271 (2013.01); **H01H 71/526** (2013.01); **H01H 5/045** (2013.01); **H01H 71/2463** (2013.01); **H01H 2001/508** (2013.01); **H01H 2300/048** (2013.01)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

Designated validation state (EPC)
KH MA MD TN

DOCDB simple family (publication)
DE 102020210028 A1 20220210; CN 115298789 A 20221104; EP 4176459 A1 20230510; EP 4176459 B1 20240828; WO 2022028849 A1 20220210

DOCDB simple family (application)
DE 102020210028 A 20200807; CN 202180021241 A 20210715; EP 2021069763 W 20210715; EP 21746413 A 20210715