

Title (en)

METHOD AND SYSTEM FOR IMPLEMENTATION OF AN INDUSTRIAL PROCESS

Title (de)

VERFAHREN UND ANLAGE ZUR DURCHFÜHRUNG EINES INDUSTRIEPROZESSES

Title (fr)

PROCÉDÉ ET INSTALLATION DESTINÉS À LA MISE EN OEUVRE D'UN PROCESSUS INDUSTRIEL

Publication

EP 4189311 B1 20240828 (DE)

Application

EP 21739562 A 20210707

Priority

- EP 20020350 A 20200803
- EP 2021025248 W 20210707

Abstract (en)

[origin: WO2022028732A1] The present invention relates to a method for conducting an industrial process (100), in which impure argon is discharged from a process step (10), in which the impure argon or part thereof is processed (20) so as to result in pure argon, and in which the pure argon or part thereof is fed back to the process step (10), wherein the processing (20) comprises a compression (21), a heat exchange (22) and a rectification (23) in a rectification column (24) column having a reboiler (25) and a tops condenser (26), the impure argon discharged from process step (10), or part thereof, is subjected to the compression (21), to the heat exchange (22) with cooling, and to at least partial condensation in the reboiler (25) to obtain an impure argon condensate, a first part of the impure argon condensate being fed into the rectification column (24) in condensed form, and a second part of the impure argon condensate being subjected to evaporation in the tops condenser (26), and the evaporated second portion of the impure argon condensate, or part thereof, being fed back to the rectification (23) as circulation stream. What is envisaged within the scope of the invention is that the circulation stream at least in part is subjected to the compression (21) together with the impure argon discharged from process step (10) or together with the part thereof that has been subjected to the compression (21). The pure argon is provided using a bottom product that is formed in the rectification (23), wherein, after removal and prior to heating, the bottom product that is formed in the rectification (23) or part thereof is subjected to heating in the heat exchange (22), and the bottom product formed in the rectification (23) or part thereof which has been subjected to heating in the heat exchange (22) is subjected to evaporation in the tops condenser (26). The present invention also relates to a corresponding plant.

IPC 8 full level

F25J 3/08 (2006.01)

CPC (source: EP)

F25J 3/08 (2013.01); **F25J 2200/02** (2013.01); **F25J 2200/40** (2013.01); **F25J 2200/50** (2013.01); **F25J 2200/72** (2013.01); **F25J 2205/40** (2013.01); **F25J 2205/66** (2013.01); **F25J 2205/82** (2013.01); **F25J 2210/42** (2013.01); **F25J 2215/58** (2013.01); **F25J 2250/02** (2013.01); **F25J 2250/20** (2013.01); **F25J 2260/58** (2013.01); **F25J 2270/02** (2013.01); **F25J 2270/88** (2013.01); **F25J 2270/904** (2013.01)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

WO 2022028732 A1 20220210; EP 4189311 A1 20230607; EP 4189311 B1 20240828; TW 202212754 A 20220401

DOCDB simple family (application)

EP 2021025248 W 20210707; EP 21739562 A 20210707; TW 110125812 A 20210714