

Title (en)

RADAR SYSTEM, ANTENNA ARRAY FOR A RADAR SYSTEM, VEHICLE HAVING AT LEAST ONE RADAR SYSTEM, AND METHOD FOR OPERATING AT LEAST ONE RADAR SYSTEM

Title (de)

RADARSYSTEM, ANTENNENARRAY FÜR EIN RADARSYSTEM, FAHRZEUG MIT WENIGSTENS EINEM RADARSYSTEM UND VERFAHREN ZUM BETREIBEN WENIGSTENS EINES RADARSYSTEMS

Title (fr)

SYSTÈME RADAR, RÉSEAU D'ANTENNES POUR UN SYSTÈME RADAR, VÉHICULE MUNI D'AU MOINS UN SYSTÈME RADAR ET PROCÉDÉ POUR FAIRE FONCTIONNER AU MOINS UN SYSTÈME RADAR

Publication

**EP 4189777 A2 20230607 (DE)**

Application

**EP 21749603 A 20210727**

Priority

- DE 102020119936 A 20200729
- EP 2021070911 W 20210727

Abstract (en)

[origin: WO2022023297A2] The invention relates to a radar system for monitoring at least one monitored region for objects (18), an antenna array (22), a vehicle, and a method for operating a radar system (12). The radar system comprises a plurality of transmitting antennas (26), which can be controlled by means of respective transmission signals and by means of which corresponding radar signals can be transmitted into at least one monitored region. Furthermore, the radar system comprises a plurality of receiving antennas (28), by means of which echos of transmitted radar signal can be received and converted into corresponding reception signals. The radar system additionally comprises at least one control and evaluation device (24), which is connected to the transmitting antennas (26) and to the receiving antennas (28) and by means of which transmission signals for the control of the transmitting antennas can be generated and by means of which object information ( $r, \varphi, \Theta$ ) of objects (18) detected by means of the radar signals (30) can be determined from reception signals. The respective phase centers (32) of at least four receiving antennas (28) are arranged on an imaginary receiver longitudinal axis (46). The respective phase centers (32) of at least two adjacent receiving antennas (28) are arranged at a base distance (40) from each other. The respective phase centers (32) of at least two adjacent receiving antennas (28) are arranged at a respective receiver longitudinal distance (48a, 48b, 48c) from each other, each receiver longitudinal distance being greater than the base distance (40).

IPC 8 full level

**H01Q 21/06** (2006.01); **G01S 13/02** (2006.01)

CPC (source: EP KR)

**G01S 13/003** (2013.01 - KR); **G01S 13/536** (2013.01 - KR); **G01S 13/931** (2013.01 - KR); **H01Q 1/3233** (2013.01 - EP KR);  
**H01Q 21/08** (2013.01 - EP KR); **B60W 2420/408** (2024.01 - KR); **G01S 2013/0254** (2013.01 - EP KR)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

Designated validation state (EPC)

KH MA MD TN

DOCDB simple family (publication)

**DE 102020119936 A1 20220203**; CN 116195139 A 20230530; EP 4189777 A2 20230607; JP 2023535509 A 20230817;  
KR 20230043991 A 20230331; WO 2022023297 A2 20220203; WO 2022023297 A3 20220324

DOCDB simple family (application)

**DE 102020119936 A 20200729**; CN 202180064798 A 20210727; EP 2021070911 W 20210727; EP 21749603 A 20210727;  
JP 2023506070 A 20210727; KR 20237007183 A 20210727