

Title (en)

HEAT GENERATING BODY, HEAT GENERATING BODY ASSEMBLY AND HEATING DEVICE

Title (de)

WÄRMEERZEUGUNGSKÖRPER, WÄRMEERZEUGUNGSKÖRPERANORDNUNG UND HEIZVORRICHTUNG

Title (fr)

CORPS DE GÉNÉRATION DE CHALEUR, ENSEMBLE DE CORPS DE GÉNÉRATION DE CHALEUR ET DISPOSITIF DE CHAUFFAGE

Publication

EP 4190191 A1 20230607 (EN)

Application

EP 21873893 A 20210527

Priority

- CN 202011066148 A 20200930
- CN 2021096296 W 20210527

Abstract (en)

A heat generating body (100, 200), a heat generating assembly (10, 20) and a heating device. The heat generating body (100, 200) comprises a base body (110, 210), a heat generating circuit (130, 230) and a temperature measuring circuit (150, 250). The base body (110, 210) is provided with a bottom surface (115), the base body (110, 210) is provided with a heat generating area (119, 319) and an electrode arrangement area (117) adjacent to the heat generating area (119, 319), and the electrode arrangement area (117) is close to the bottom surface (115) compared with the heat generating area (119, 319); the heat generating circuit (130, 230) is located on the base body (110, 210), and the heat generating circuit (130, 230) comprises a heat generating part (131, 231) and a heat generating electrode (133, 233) electrically connected to the heat generating part (131, 231), the heat generating part (131, 231) being located in the heat generating area (119, 319), and the heat generating electrode (133, 233) being located in the electrode arrangement area (117); the temperature measuring circuit (150, 250) is located on the base body (110, 210), the temperature measuring circuit (150, 250) and the heat generating circuit (130, 230) are arranged spaced apart, and the temperature measuring circuit (150, 250) comprises a temperature measuring part (151, 251, 351) and a temperature measuring electrode (153, 253) electrically connected to the temperature measuring part (151, 251, 351); and the heat generating area (119, 319) comprises a high-temperature area (119a), and the temperature measuring part (151, 251, 351) is located in the high-temperature area (119a). In an initial heating stage of the heat generating body (100, 200), the deviation between an actual temperature and a planned temperature is small.

IPC 8 full level

A24F 40/57 (2020.01); **A24F 40/40** (2020.01)

CPC (source: CN EP KR)

A24F 40/40 (2020.01 - CN); **A24F 40/46** (2020.01 - CN EP KR); **A24F 40/50** (2020.01 - CN KR); **A24F 40/51** (2020.01 - EP);

A24F 40/53 (2020.01 - CN KR); **A24F 40/57** (2020.01 - CN KR); **H05B 3/0019** (2013.01 - KR); **H05B 3/03** (2013.01 - KR);

H05B 3/42 (2013.01 - KR); **H05B 3/46** (2013.01 - EP); **H05B 3/48** (2013.01 - EP); **A24F 40/20** (2020.01 - EP); **A24F 40/51** (2020.01 - KR);

H05B 2203/013 (2013.01 - EP); **H05B 2203/016** (2013.01 - EP)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

Designated validation state (EPC)

KH MA MD TN

DOCDB simple family (publication)

EP 4190191 A1 20230607; CN 112244359 A 20210122; JP 2023528910 A 20230706; JP 7516570 B2 20240716; KR 20230016681 A 20230202; WO 2022068231 A1 20220407

DOCDB simple family (application)

EP 21873893 A 20210527; CN 202011066148 A 20200930; CN 2021096296 W 20210527; JP 2022574737 A 20210527; KR 20227045954 A 20210527