

Title (en)
FLAT KEY FOR A CYLINDER LOCK

Title (de)
FLACHSCHLÜSSEL FÜR EINEN SCHLIESSZYLINDER

Title (fr)
CLÉ PLATE POUR CYLINDRE DE SERRURE

Publication
EP 4204648 B1 20240131 (DE)

Application
EP 22817625 A 20221111

Priority
• AT 502322021 U 20211115
• EP 2022081619 W 20221111

Abstract (en)
[origin: WO2023084022A1] A flat key (1) for a locking cylinder (101) has substantially flat and approximately parallel flat key sides (2', 3'), a key rear section (4), and a key front section (5) opposite thereto. The key front section (5) has a toothing that is used to position tumbler pins which are divided into core pins (112) and housing pins (111) and which are spring-loaded against the key front section (5) in the direction of the key rear section (4) and into corresponding bores. Grooves (11', 12', 13', 14', 20'-25') in the form of profiled variation elements and profiled guiding elements are provided in the flat sides (2', 3') of the flat key (1), wherein at least two grooves (11', 12') of one flat side (3') of the flat key (1), which are preferably part of the profiled guide, overlap and are undercut in opposite directions. According to the invention, a depression (15', 16') is provided in the outer flank (11a', 12a') of at least one of the two grooves (11', 12'), preferably both grooves (11', 12'), at least one region (15b, 16b) of said depression not being visible from the side. The two depressions (15', 16') are preferably symmetrical so that the depressions can be produced using a T-slot milling cutter (60). Such flat keys (1) cannot be completely measured from the side even when using a laser scanner but can still be produced solely by milling.

IPC 8 full level
E05B 19/00 (2006.01); **E05B 27/00** (2006.01)

CPC (source: AT EP)
E05B 19/0029 (2013.01 - AT EP); **E05B 27/0042** (2013.01 - AT EP)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC ME MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
WO 2023084022 A1 20230519; AU 2022388777 A1 20240523; DK 4204648 T3 20240408; EP 4204648 A1 20230705; EP 4204648 B1 20240131; ES 2975252 T3 20240704; FI 4204648 T3 20240417; HR P20240470 T1 20240705; PL 4204648 T3 20240520; SI 4204648 T1 20240531

DOCDB simple family (application)
EP 2022081619 W 20221111; AU 2022388777 A 20221111; DK 22817625 T 20221111; EP 22817625 A 20221111; ES 22817625 T 20221111; FI 22817625 T 20221111; HR P20240470 T 20221111; PL 22817625 T 20221111; SI 202230030 T 20221111