

Title (en)

RECEIVING STATE INDICATION METHOD FOR A-MPDU AND RECEIVE END DEVICE

Title (de)

EMPFANGSSTATUSANZEIGEVERFAHREN FÜR A-MPDU UND EMPFANGSSEITIGE VORRICHTUNG

Title (fr)

PROCÉDÉ D'INDICATION D'ÉTAT DE RÉCEPTION POUR UNE A-MPDU ET DISPOSITIF D'EXTRÉMITÉ DE RÉCEPTION

Publication

EP 4224756 A3 20231108 (EN)

Application

EP 23165368 A 20160602

Priority

- CN 201510551675 A 20150901
- EP 21185717 A 20160602
- EP 16840643 A 20160602
- CN 2016084576 W 20160602

Abstract (en)

The present invention provides a receiving state indication method for an A-MPDU and a receiving device, so as to indicate a receiving state of an A-MPDU including an MSDU fragment. The method in the present invention includes: receiving, by a receive end, an A-MPDU sent by a transmit end; and when determining that at least one MPDU in the A-MPDU is obtained by encapsulating a fragment of an MSDU, sending, by the receive end to the transmit end, an acknowledgement frame used to indicate a receiving state of the A-MPDU, where the acknowledgement frame includes a fragment indication field and a receiving state field, the fragment indication field is used to indicate that the A-MPDU includes an MPDU obtained by encapsulating an MSDU fragment, the receiving state field is used to indicate a receiving state of each MPDU in the A-MPDU, and a specified bit quantity of bits in the receiving state field is used to indicate receiving states of MPDUs with a same sequence number SN.

IPC 8 full level

H04L 1/16 (2023.01); **H04L 1/00** (2006.01)

CPC (source: CN EP KR US)

H04L 1/0023 (2013.01 - CN); **H04L 1/0036** (2013.01 - CN); **H04L 1/1614** (2013.01 - EP KR US); **H04L 1/1621** (2013.01 - EP US);
H04L 1/1628 (2013.01 - KR); **H04W 28/06** (2013.01 - US); **H04W 72/21** (2023.01 - US)

Citation (search report)

- [XII] US 2013223345 A1 20130829 - ASTERJADHI ALFRED [NL], et al
- [A] ALFRED ASTERJADHI (QUALCOMM INC). "LB200-MAC-Resolution-Clause-8.3.5.1.5 ; 11-13-1427-00-00ah-lb200-mac-resolution-clause-8-3-5-1-5", IEEE DRAFT; 11-13-1427-00-00AH-LB200-MAC-RESOLUTION-CLAUSE-8-3-5-1-5, IEEE-SA MENTOR, PISCATAWAY, NJ USA, vol. 802.11ah, 13 November 2013 (2013-11-13), pages 1 - 6, XP068063456

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 3313012 A1 20180425; EP 3313012 A4 20180822; EP 3313012 B1 20210804; CN 106487476 A 20170308; CN 106487476 B 20201009;
CN 112511267 A 20210316; CN 112511267 B 20220422; EP 3982576 A1 20220413; EP 3982576 B1 20230531; EP 4224756 A2 20230809;
EP 4224756 A3 20231108; ES 2886363 T3 20211217; JP 2018532353 A 20181101; JP 6568657 B2 20190828; KR 102116361 B1 20200528;
KR 20180026518 A 20180312; US 10574398 B2 20200225; US 11075717 B2 20210727; US 2018183548 A1 20180628;
US 2020153553 A1 20200514; WO 2017036214 A1 20170309

DOCDB simple family (application)

EP 16840643 A 20160602; CN 201510551675 A 20150901; CN 2016084576 W 20160602; CN 202010997797 A 20150901;
EP 21185717 A 20160602; EP 23165368 A 20160602; ES 16840643 T 20160602; JP 2018529700 A 20160602; KR 20187003392 A 20160602;
US 201815904031 A 20180223; US 202016747368 A 20200120