

Title (en)

METHOD FOR MANUFACTURING A SPRING LEAF OF A TIMEPIECE MEMBER AND SAID SPRING LEAF

Title (de)

VERFAHREN ZUR HERSTELLUNG EINES FEDERBLATTES EINES UHRENELEMENTS UND BESAGTES FEDERBLATT

Title (fr)

PROCEDE DE FABRICATION D'UNE LAME RESSORT D'UN ORGANE HORLOGER ET LADITE LAME RESSORT

Publication

EP 4248277 A1 20230927 (FR)

Application

EP 21811050 A 20211116

Priority

- EP 20208118 A 20201117
- EP 2021081903 W 20211116

Abstract (en)

[origin: WO2022106433A1] The present invention relates to a method for manufacturing a spring leaf (4) of a timepiece member (1) pivoting about a swivel axis and subjected to a torque exerted by at least one spring leaf (4), said timepiece member (1) comprising at least one rotary mobile portion configured so as to be capable of pivoting about the swivel axis thereof, said spring leaf (4) being configured so as to work within a predetermined range of angular positions adopted by the end of the spring leaf (4) in association with the rotary mobile portion during an angular displacement of at least said end of the spring leaf (4), which method comprises the steps of: (a) determining objectives to be achieved by said spring leaf (4); (b) determining fixed parameters relating to the spring leaf (4); (c) determining variable parameters relating to the spring leaf (4); (d) providing a substrate made of a material from which the spring leaf (4) is produced so as to achieve the objectives predetermined in step (a) and the fixed and variable parameters predetermined in steps (b) and (c); (e) generating geometric shapes of the spring leaf (4), the geometric shape of the spring leaf (4) in the neutral state being a curve defined by the equation (1), (1) with $u = (r_{\max} - r)/(r_{\max} - r_{\min}) \in [0,1]$, where r_{\min} and r_{\max} are the distances between the swivel axis of the timepiece member (1) and each of the ends of the spring leaf (4); B_1 and B_2 , which are variable parameters, are the angles between the ends of the spring leaf (4) and the attachment points thereof at r_{\max} and r_{\min} ; n defining the total number of curvatures; A_k , which are variable parameters, are angular amplitudes, each spring leaf shape being generated by randomly selecting values for the variable parameters and for the coefficients A_k , B_1 and B_2 within the search ranges thereof; (f) numerically calculating, for each geometric shape of a spring leaf (4) generated in step (e), at least the torque, the stress and the space occupied by the deformed portion; (g) selecting, from the results of the calculations of step (f), the best permissible geometric shapes obtained in step (e) and optimising said permissible geometric shapes corresponding to the equation (1), so as to identify the variable parameters and A_k , B_1 and B_2 whereby the spring leaf shape (4) that best achieves the objectives predetermined in step (a) can be obtained, the optimisation parameters being selected from the variable parameters predetermined in step (c) and the coefficients A_k , B_1 and B_2 ; (h) forming at least one spring leaf (4) having the shape obtained in step (g) in said substrate.

IPC 8 full level

G04B 1/10 (2006.01); **G04B 17/04** (2006.01)

CPC (source: CH EP)

G04B 1/105 (2013.01 - EP); **G04B 1/145** (2013.01 - CH EP); **G04B 1/16** (2013.01 - CH); **G04B 17/045** (2013.01 - CH); **G04B 17/066** (2013.01 - EP)

Citation (search report)

See references of WO 2022106433A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

Designated validation state (EPC)

KH MA MD TN

DOCDB simple family (publication)

WO 2022106433 A1 20220527; CH 718065 A2 20220531; EP 4248277 A1 20230927

DOCDB simple family (application)

EP 2021081903 W 20211116; CH 0705662021 A 20211116; EP 21811050 A 20211116