

Title (en)  
FILTER SEGMENT MANUFACTURING METHOD AND MANUFACTURING APPARATUS

Title (de)  
VERFAHREN UND VORRICHTUNG ZUR HERSTELLUNG VON FILTERSEGMENTEN

Title (fr)  
PROCÉDÉ DE FABRICATION D'UN SEGMENT DE FILTRE ET APPAREIL DE FABRICATION

Publication  
**EP 4256981 A4 20240828 (EN)**

Application  
**EP 20964270 A 20201203**

Priority  
JP 2020044954 W 20201203

Abstract (en)  
[origin: EP4256981A1] Provided is a manufacturing method for a filter segment that suppresses the displacement of a breakable capsule even when an external force is applied thereto. The manufacturing method for a filter segment according to the present invention is a method of manufacturing a filter segment for a tobacco product, including the steps of: applying a plasticizer to one or more breakable capsules held on the rim of an insertion wheel and to the rim of the insertion wheel; and burying the rim of the insertion wheel in a fiber bundle that extends in a direction tangential to the insertion wheel and allowing to release the breakable capsules, thereby embedding the breakable capsules in the fiber bundle.

IPC 8 full level  
**A24D 3/02** (2006.01)

CPC (source: EP)  
**A24D 3/0216** (2013.01); **A24D 3/022** (2013.01); **A24D 3/0275** (2013.01); **A24D 3/048** (2013.01); **A24D 3/061** (2013.01); **A24D 3/14** (2013.01)

Citation (search report)  
[A] US 2012080043 A1 20120405 - NAENEN RENE [BE], et al

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)  
**EP 4256981 A1 20231011**; **EP 4256981 A4 20240828**; JP 7420974 B2 20240123; JP WO2022118417 A1 20220609;  
WO 2022118417 A1 20220609

DOCDB simple family (application)  
**EP 20964270 A 20201203**; JP 2020044954 W 20201203; JP 2022566566 A 20201203