

Title (en)  
HYBRID TELECOMMUNICATION CABLE

Title (de)  
HYBRIDES NACHRICHTENKABEL

Title (fr)  
CÂBLE DE TÉLÉCOMMUNICATION HYBRIDE

Publication  
**EP 4268001 A1 20231101 (FR)**

Application  
**EP 21840915 A 20211220**

Priority  
• FR 2013882 A 20201222  
• EP 2021086699 W 20211220

Abstract (en)  
[origin: WO2022136217A1] The invention relates to an, in particular undersea, telecommunication cable (1, 100) comprising: • a core (2) comprising a plurality of optical fibres (3), • an inner reinforcement (7) radially arranged around the core (2), the inner reinforcement (7) comprising a plurality of steel wires (8), • an intermediate sheath (6) arranged radially between the core (2) and the inner reinforcement (7), and • a protective sheath (9) made of polymer material arranged radially around the inner reinforcement (7), characterised in that the cable (1, 100) further comprises at least one optical fibre sensor (10, 12) arranged between the core (2) and the protective sheath (9). The invention also relates to a method for measuring mechanical deformations undergone by such a telecommunication cable.

IPC 8 full level  
**G02B 6/44** (2006.01)

CPC (source: EP US)  
**G01B 11/16** (2013.01 - US); **G01D 5/35361** (2013.01 - US); **G02B 6/4416** (2013.01 - US); **G02B 6/4427** (2013.01 - EP US);  
**G02B 6/4432** (2013.01 - US); **G02B 6/4416** (2013.01 - EP); **G02B 6/443** (2013.01 - EP)

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)  
BA ME

Designated validation state (EPC)  
KH MA MD TN

DOCDB simple family (publication)  
**FR 3118205 A1 20220624**; CN 116710824 A 20230905; EP 4268001 A1 20231101; JP 2024501375 A 20240111; US 2024045163 A1 20240208;  
WO 2022136217 A1 20220630

DOCDB simple family (application)  
**FR 2013882 A 20201222**; CN 202180087408 A 20211220; EP 2021086699 W 20211220; EP 21840915 A 20211220;  
JP 2023563151 A 20211220; US 202118258818 A 20211220