

Title (en)

REFRIGERATION APPLIANCE WITH FLEXIBLE DRAWER CAPACITY

Title (de)

KÄLTEGERÄT MIT FLEXIBLER SCHUBLADENKAPAZITÄT

Title (fr)

APPAREIL FRIGORIFIQUE À CAPACITÉ DE TIROIR FLEXIBLE

Publication

EP 4285060 A1 20231206 (EN)

Application

EP 21702616 A 20210127

Priority

EP 2021051874 W 20210127

Abstract (en)

[origin: WO2022161603A1] Refrigeration Appliance with Flexible Drawer Capacity The invention relates to a refrigeration appliance, in particular a refrigerator or a fridge-freezer (2). The refrigeration appliance comprises a housing (4), a refrigerating compartment (6) formed within the housing (4), a slidably and releasably supported first drawer (20a) having a first vertical extension, a second slidably and releasably supported second drawer (20b) having a second vertical extension being greater than the first vertical extension of the first drawer (20a), and a first, a second and a third drawer support position (72a, 72b, 74a, 74b, 76a, 76b), wherein in vertical direction the first drawer support position (72a, 72b) is higher than the second drawer support position (74a, 74b) and the second drawer support position (74a, 74b) is higher than the third drawer support position (76a, 76b). When A) the first or second drawer (20a, 20b) is supported at the first drawer support position (72b) the upper levels of the first and second drawers (20a, 20b) are at the same vertical position within the refrigerating compartment (6), and when the first drawer (20a) is supported at the third drawer support position (76b) or when the second drawer (20b) is supported at the second drawer support position (74b) the lower levels of the first and second drawers (20a, 20b) are at the same vertical position within the refrigerating compartment (6), or when B) the first or second drawer (20a, 20b) is supported at the third drawer support position (76a) the upper levels of the first and second drawers (20a, 20b) are at the same vertical position within the refrigerating compartment (6), and when the first drawer (20a) is supported at the second drawer support position (74a) or when the second drawer (20b) is supported at the first drawer support position (72a) the lower levels of the first and second drawers (20a, 20b) are at the same vertical position within the refrigerating compartment (6).

IPC 8 full level

F25D 25/02 (2006.01); **F25D 23/06** (2006.01)

CPC (source: EP US)

F25D 17/042 (2013.01 - EP US); **F25D 17/065** (2013.01 - US); **F25D 23/067** (2013.01 - EP US); **F25D 25/025** (2013.01 - EP US);
F25D 2317/041 (2013.01 - US)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

Designated validation state (EPC)

KH MA MD TN

DOCDB simple family (publication)

WO 2022161603 A1 20220804; CN 116802448 A 20230922; EP 4285060 A1 20231206; US 2024060711 A1 20240222

DOCDB simple family (application)

EP 2021051874 W 20210127; CN 202180092039 A 20210127; EP 21702616 A 20210127; US 202118270262 A 20210127