

Title (en)  
CLOSED, GASTIGHT SYSTEM AND METHOD FOR GAINING SELLABLE PETROLEUM COKE PIECES OUT OF SOLIDIFIED PETROLEUM COKE IN A COKE DRUM UNIT

Title (de)  
GESCHLOSSENES GASDICHTES SYSTEM UND VERFAHREN ZUR GEWINNUNG VON VERMARKTUNGSFÄHIGEN ERDÖLKOKSSTÜCKEN AUS VERFESTIGTEM ERDÖLKOKS IN EINER KOKSTROMMELEINHEIT

Title (fr)  
SYSTÈME FERMÉ ET ÉTANCHE AUX GAZ ET PROCÉDÉ D'OBTENTION DE PIÈCES DE COKE DE PÉTROLE POUVANT ÊTRE VENDUS À PARTIR DE COKE DE PÉTROLE SOLIDIFIÉ DANS UNE UNITÉ DE TAMBOUR À COKE

Publication  
**EP 4306617 A1 20240117 (EN)**

Application  
**EP 22184299 A 20220712**

Priority  
EP 22184299 A 20220712

Abstract (en)  
A closed, gastight system for gaining sellable petroleum coke pieces out of solidified petroleum coke in a coke drum unit according to the invention is configured to be connected to a coke drum unit (X) containing solidified petroleum coke and comprises a coke crushing unit (C) for crushing the petroleum coke into sellable petroleum coke pieces, configured to be connected to the coke drum unit (X), particularly by means of a flexible transition piece (A); a line, particularly a closed sluice way (D) leading petroleum coke slurry to a closed slurry basin; a closed slurry basin (E); a dewatering bin unit (G) configured to receive the petroleum coke slurry from the slurry basin (E), to collect the sellable petroleum coke pieces, and to act as a filter leading runoff drain water from a lower area thereof as filtered water and petroleum coke fines out of it; a closed drain water basin (I), separate from the slurry basin (E), configured to receive the filtered water and the petroleum coke fines from the dewatering bin unit (G); a single water tank (L) configured to receive the filtered water from the drain water basin (I); a hot quench water draining line (2) configured to receive hot quench water from the coke drum unit (X) and to lead the same to the closed slurry basin (E); and a cooling water line (3) leading from the water tank (L), particularly from an intermediate portion thereof, to the hot quench water draining line (2), in particular to a joining point (JP) in the hot quench water draining line (2) at a position above the closed slurry basin (E), configured to feed cooling water from the water tank (L) to the hot quench water in the hot quench water draining line (2), in order to prevent steam generation within the slurry basin (E).

IPC 8 full level  
**C10B 33/00** (2006.01); **C10B 39/04** (2006.01)

CPC (source: EP)  
**C10B 33/003** (2013.01); **C10B 39/04** (2013.01); **C10B 55/00** (2013.01)

Citation (applicant)  
EP 2707458 A1 20140319 - TRIPLAN AG [DE]

Citation (search report)  

- [YA] WO 2018001462 A1 20180104 - TRIPLAN AG [DE]
- [YA] US 2007262032 A1 20071115 - WANG HUALIN [CN], et al
- [A] CN 106398743 A 20170215 - LUOYANG JIANGUANG SPECIAL EQUIPMENT CO LTD
- [A] N.N.: "Trust our KREBS Cyclone Close Packed", 1 January 2021 (2021-01-01), XP055982546, Retrieved from the Internet <URL:https://www.flsmidth.com/-/media/brochures/brochures-products/centrifugation-and-classification/2021/krebs-cp-vessels-for-oil-refinery-applications.pdf> [retrieved on 20221117]

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)  
BA ME

Designated validation state (EPC)  
KH MA MD TN

DOCDB simple family (publication)  
**EP 4306617 A1 20240117**; **EP 4306617 B1 20240327**; **EP 4306617 C0 20240327**; EP 4365266 A2 20240508; EP 4365266 A3 20240731

DOCDB simple family (application)  
**EP 22184299 A 20220712**; EP 24166178 A 20220712