

Title (en)
COPPER ALLOY WIRE

Title (de)
KUPFERLEGIERUNGSDRAHT

Title (fr)
FIL D'ALLIAGE DE CUIVRE

Publication
EP 4317493 A1 20240207 (EN)

Application
EP 22775653 A 20220323

Priority
• JP 2021048044 A 20210323
• JP 2022013377 W 20220323

Abstract (en)
Provided is a copper alloy wire rod superior in the balance of the strength, the electric conductivity and the drawability. A copper alloy wire rod comprises an alloy composition including 1.0% by mass or more and 6.0% by mass or less of Ag, a remainder being Cu and inevitable impurities, in which, for a peak intensity I(111) of 111 diffraction, a peak intensity I(200) of 200 diffraction, a peak intensity I(220) of 220 diffraction and a peak intensity I(311) of 311 diffraction obtained by X-ray diffraction analysis of a surface, a peak intensity ratio of a total intensity of the peak intensity I(111), the peak intensity I(200) and the peak intensity I(311) relative to the peak intensity I(220) ((the peak intensity I(111) + the peak intensity I(200) + the peak intensity I(311)) / the peak intensity I(220)) is 1.20 or more and 3.00 or less.

IPC 8 full level
C22C 9/00 (2006.01); **C22F 1/00** (2006.01); **C22F 1/08** (2006.01)

CPC (source: EP KR)
C22C 9/00 (2013.01 - EP KR); **C22F 1/08** (2013.01 - EP KR)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

Designated validation state (EPC)
KH MA MD TN

DOCDB simple family (publication)
EP 4317493 A1 20240207; CN 115427595 A 20221202; JP WO2022202871 A1 20220929; KR 20230024244 A 20230220;
WO 2022202871 A1 20220929

DOCDB simple family (application)
EP 22775653 A 20220323; CN 202280003421 A 20220323; JP 2022013377 W 20220323; JP 2022542346 A 20220323;
KR 20227031179 A 20220323