

Title (en)

LAND VEHICLE WITH A FRONT COMPARTMENT SEALED BY A GASKET BEARING ON A QUASI-CONTINUOUS BEARING SURFACE

Title (de)

LANDFAHRZEUG MIT EINEM FRONTRAUM, DER DURCH EINE DICHTUNG ABGEDICHTET IST, DIE AUF EINER QUASIKONTINUIERLICHEN LAGERFLÄCHE GELAGERT IST

Title (fr)

VÉHICULE TERRESTRE À COMPARTIMENT AVANT ÉTANCHÉIFIÉ PAR UN JOINT APPUYÉ SUR UNE SURFACE D'APPUI QUASI-CONTINUE

Publication

EP 4326581 A1 20240228 (FR)

Application

EP 22713988 A 20220315

Priority

- FR 2104055 A 20210419
- FR 2022050465 W 20220315

Abstract (en)

[origin: WO2022223897A1] The invention relates to a land vehicle which comprises a bumper frame (AP) comprising an upper edge (BS) having two ends (E), right and left, secured to which are brackets (PF) for attaching optical units (BO) each comprising an upper face (FS), and a front bonnet comprising an inner face which covers, in the closed position, a front compartment (CM) by having a sub-portion extending above the upper edge (BS) and upper faces (FS). Each attachment bracket (PF) comprises a bearing wall (PP) which extends the upper edge (BS) at the corresponding end (E) towards the upper face (FS) of its optical unit (BO). A sealing gasket (JE) is secured to the sub-portion of the inner face or to the upper edge (BS), bearing walls (PP) and upper faces (FS), in order to provide the seal in the upper front part (PS) of the front compartment (CM).

IPC 8 full level

B60J 10/84 (2016.01); **B60Q 1/04** (2006.01)

CPC (source: EP)

B60J 10/84 (2016.02); **B60Q 1/0466** (2013.01); **B60Q 1/0491** (2013.01)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

Designated validation state (EPC)

KH MA MD TN

DOCDB simple family (publication)

FR 3121905 A1 20221021; FR 3121905 B1 20230303; EP 4326581 A1 20240228; WO 2022223897 A1 20221027

DOCDB simple family (application)

FR 2104055 A 20210419; EP 22713988 A 20220315; FR 2022050465 W 20220315